

113033

CP35G/G6

GN2/3 FREESTANDING SINGLE TANK GAS PASTA COOKER (23 L) ON CLOSED CABINET - BASKETS NOT INCLUDED



- Freestanding gas pasta cooker (23 l) GN2/3 on a closed cabinet (35 cm).
- Stainless steel control panel and side panels.
- Module coupling system with external side joints.
- A pasta cooker is also used to boil rice, vegetables, meat and other products.
- The deep drawn tank with rounded corners is seamlessly welded to an AISI 304 top, Scotch Brite finish.
- AISI 316 stainless steel tank, drainpipe, and false bottom for long-lasting resistance against salt corrosion.
- Water filling control inside the control panel with water injector inside the tank.
- Heating through a 10 kW tubular burner with adjustment through valved cock.
- Piezoelectric ignition.
- Pilot burner and safety thermocouple.
- Safety thermostat to protect the tank against ignition without water or excessive evaporation.
- Overflow for draining starch in the front part of the tank.
- Bottom drain.
- Baskets not included.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests
- The equipment is delivered in accordance with the customer's specifications in terms of installed nozzles, even during testing. G20 natural gas is the standard configuration. In addition, spare nozzles are included should conversion be necessary on site.



TECHNICAL DATA

| TOTAL POWER | 10 kW | GAS POWER | 10 kW |
|-----------------------------|---------------|------------------------------|----------------------|
| TANK CAPACITY | 23lt | LOADING WATER | Injector in the tank |
| NATURAL GAS CONSUMPTION | 1,05 m³/h | LPG CONSUMPTION | 0.79 m³/h |
| TANK DIMENSIONS | 30,5x34x29 cm | TANK TYPE | AISI 316 |
| CE GAS CERTIFICATE NUMBER | CE-0085BO0097 | WATER CONNECTION POSITION | Bottom |
| WATER DRAIN POSITION | Bottom | GAS CONNECTION DIAMETER | 1/2"G EN10226-1 |
| GAS CONNECTION HEIGHT (H) | 0 mm | GAS CONNECTION HEIGHT (X) | 230 mm |
| GAS CONNECTION HEIGHT (Y) | -270 mm | WATER CONNECTION DIAMETER | 1/2" |
| WATER CONNECTION HEIGHT (H) | 0 mm | WATER CONNECTION HEIGHT (X) | 230 mm |
| WATER CONNECTION HEIGHT (Y) | -120 mm | DRAIN DIAMETER | 1" |
| DRAIN CONNECTION HEIGHT (H) | 0 mm | DRAIN CONNECTION HEIGHT (X) | 120 mm |
| DRAIN CONNECTION HEIGHT (Y) | -310 mm | FOOT HEIGHT | 155 mm |
| FOOT ADJUSTMENT | 155/250 mm | IPX RATING | 4 |
| WIDTH | 35 cm | DEPTH | 60 cm |
| HEIGHT | 85 cm | PACKAGE WIDTH | 76,0 cm |
| PACKAGE DEPTH | 42 cm | PACKAGE HEIGHT | 118 cm |
| NET WEIGHT | 39 kg | GROSS WEIGHT | 48 kg |
| VOLUME | 0,37 m³ | HARMONISED CODE | 84198180 |
| LATENT HEAT RELEASE | 3000.0 W | SENSIBLE HEAT RELEASE | 1000.0 W |
| STEAM RELEASE | 4410.0 g/h | | |
| | | | |

ACCESSORIES

PASTA COOKER BASKETS (2 X GN1/3) - DIM. CM (29X16X20H) PASTA COOKER BASKET (4 X GN1/6) - DIM. CM (14X14X20H) 120620

120625

PASTA COOKER BASKET (1 X GN2/3) - DIM. CM (29X29X20H) 120635

120652 PASTA COOKER LID (GN2/3)

120660 PASTA COOKER BASKET (1 X GN1/3 + 2 X GN1/6) - DIM. CM (29X16X20H) (14X14X20H)

120700 PASTA COOKER BASKET (2 X GN2/6) - DIM. CM (14.5X29X20H)



INSTALLATION SCHEMES

