


116009

PFL105E/60

## ELECTRIC COOKER WITH 6 HERMETIC ROUND HOT PLATES (DIAM 18 CM - 7.1 IN) ON ELECTRIC CONVENTION OVEN WITH 1 GRID AND 1 TRAY





- Electric cooker (105 cm) with 6 round cast iron plates (18 cm diameter) on a GN 1/1 electric convection oven.
- Deep drawn worktop featuring rounded corners to prevent overflows and ensure enhanced hygiene and easy cleaning. Made with AISI 304 stainless steel with Scotch Brite finish.
- Cast iron electric plates hermetically fixed to the deep drawn worktop.
- 2.0 kW power for each plate adjustable to 6 levels.
- Heating commands and separated controls for each plate.
- Lights warning when the plates are ignited.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
  - >> GN 1/1 ELECTRIC CONVECTION OVEN
  - >> Enamelled cooking chamber (62x41.5x30.5 cm).
- >> Oven door with 2 tempered glass panes. Heat-reflecting inner glass.
  - >> Removable silicone gasket.
  - >> Thermostatic control 0-275°C.
  - >> 4 GN 1/1 trays.
- . >> Timer 0-50 minutes.
- >> 1 grid and 1 tray included.
- Stainless steel control panel and side panels.
- Module coupling system with external side joints.



TECHNICAL DATA			
TOTAL POWER	14,5 kW	ELECTRIC POWER	14,5 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
OVEN POWER	2,5 kW	BOILING TOP POWER	12 kW
COOKING ZONE POWER	6x2 n°- kW	TRAY CAPACITY	n° 4xGN1/1
COOKING CHAMBER DIMENSIONS	62x41,5x30,5 cm	OVEN DIMENSIONS	GN1/1
ELECTRIC PLATE DIMENSIONS	Ø 18 cm	GUIDES	n° 4
NUMBER OF COOKING ZONES	n° 6	VERTICAL DISTANCE BETWEEN TRAYS	1x8 + 2x5 cm
OVEN TEMPERATURE RANGE	0÷275 °C	MINIMUM POWER CABLE CROSS-SECTION	5 x 4 n° - mm²
TIMER	0-50 min	ELECTRIC CABLE TYPE	H07 RN-F
OVEN TYPE	Convection	IPX RATING	4
WIDTH	105 cm	DEPTH	60 cm
HEIGHT	85 cm	PACKAGE WIDTH	111 cm
PACKAGE DEPTH	75,0 cm	PACKAGE HEIGHT	117 cm
NET WEIGHT	72 kg	GROSS WEIGHT	92 kg
VOLUME	0,97 m³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	1160.0 W	SENSIBLE HEAT RELEASE	2900.0 W
STEAM RELEASE	1711.0 g/h		

## **ACCESSORIES**

120585 JOINT FOR TECNO60, TECNO65 120667 BACK SPLASH GUARD L=1050MM



## **INSTALLATION SCHEMES**

