
116026

FTL70E/6/2

ELECTRIC GRIDDLE WITH SMOOTH PLATE (TOP VERSION)



- Electric griddle (70 cm top version) with a smooth steel plate.
- Horizontal cooking plate (12 cm thick).
- One temperature control.
- Power: 6 kW.
- Voltage: V 220-240.
- Stainless steel control panel and side panels.
- Module coupling system with external side joints.
- Appliances intended for direct cooking.
- Cooking plate hermetically sealed to the worktop.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 310°C.
- Grooving with a cap and removable drawer for collecting grease and liquids.
- Removable splashback on 3 sides integrated into the worktop.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Plastic feet (H=51 mm).

TECHNICAL DATA

TOTAL POWER	6 kW	ELECTRIC POWER	6 kW
FREQUENCY	50/60 Hz	VOLTAGE	220-240 ~ V
TEMPERATURE RANGE	50÷320 °C	MINIMUM POWER CABLE CROSS-SECTION	3 x 4 n° - mm ²
COOKING SURFACE	69,6x56,4 cm	ELECTRIC CABLE TYPE	H07 RN-F
PLATE TYPE	Smooth	HEATING ZONES	n° 1
ELECTRICAL CONNECTION HEIGHT (H)	0 mm	ELECTRICAL CONNECTION HEIGHT (X)	647 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-445 mm	FOOT HEIGHT	51 mm
IPX RATING	4	WIDTH	70 cm
DEPTH	60 cm	HEIGHT	30 cm
PACKAGE WIDTH	76,0 cm	PACKAGE DEPTH	71,0 cm
PACKAGE HEIGHT	53,0 cm	NET WEIGHT	54,7 kg
GROSS WEIGHT	62,2 kg	VOLUME	0,2900 m ³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	2400.0 W
SENSIBLE HEAT RELEASE	1980.0 W	STEAM RELEASE	3528.0 g/h

ACCESSORIES

120590	PAIR OF JOINTS FOR GRIDDLES
120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
120669	SPLASHBACK L=700MM FOR GRIDDLE

INSTALLATION SCHEMES

