

116031

FTC70E/6/0

## ELECTRIC GRIDDLE WITH CHROME-PLATED SMOOTH PLATE (TOP VERSION)



- Electric griddle (70 cm top version) with smooth mirror-polished brushed chrome-plated plate recommended for cooking delicate products.
- Horizontal cooking plate (12 cm thick), 2 independent work areas.
- Power: 7.8 kW.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- Scraper included.
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- Stainless steel control panel and side panels.
- Module coupling system with external side joints.
- Appliances intended for direct cooking.
- Cooking plate hermetically sealed to the worktop.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 310°C.
- Grooving with a cap and removable drawer for collecting grease and liquids.
- Removable splashback on 3 sides integrated into the worktop.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Plastic feet (H=51 mm).



51 mm

70 cm

30 cm

71,0 cm

54,7 kg

TECHNICAL DATA			
TOTAL POWER	7,8 kW	ELECTRIC POWER	7,8 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	50÷320 °C	MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm²
COOKING SURFACE	69,6x56,4 cm	ELECTRIC CABLE TYPE	H07 RN-F
PLATE TYPE	Chrome-plated - smooth	HEATING ZONES	n° 2
ELECTRICAL CONNECTION HEIGHT (H)	0 mm	ELECTRICAL CONNECTION HEIGHT (X)	647 mm

FOOT HEIGHT

PACKAGE DEPTH

**NET WEIGHT** 

WIDTH

**HEIGHT** 

## GROSS WEIGHT 62,2 kg VOLUME 0,2900 m³ HARMONISED CODE 84198180 LATENT HEAT RELEASE 3120.0 W SENSIBLE HEAT RELEASE 2574.0 W STEAM RELEASE 4586.4 g/h

## **ACCESSORIES**

**ELECTRICAL CONNECTION** 

HEIGHT (Y)
IPX RATING

PACKAGE WIDTH

PACKAGE HEIGHT

DEPTH

-445 mm

4

60 cm

76,0 cm

53,0 cm

120590 PAIR OF JOINTS FOR GRIDDLES
120595 GRIDDLE-CLEANING SCRAPER
120597 SCRAPER - SPARE BLADE KIT (10 PCS)
120669 SPLASHBACK L=700MM FOR GRIDDLE



## **INSTALLATION SCHEMES**

775 - REG FT E/6/ - FT E/ INGRESSO CAVO ELETTRICO ELECTRIC CABLE INLET INGRESSO CAVO ELETTRICO ELECTRIC CABLE INLET 650 44 50 58 **†**6† 5415.679.00 182 LL 53 89 350 - 700 EQUIPOTENZIALE -EQUIPOTENTIAL Data scarque | Print da le 16.04.14 52 ÷ 32 944 23 89 350 - 700 EQUIPOTENZIALE EQUIPOTENTIAL INGRESSO CAVO ELETTRICO ELECTRIC CABLE INLET 330 28 INGRESSO CAVO ELETTRICO ELECTRIC CABLE INLET 4 900 300 - FIX