

116032

FTC70E/6/2

ELECTRIC GRIDDLE WITH CHROME-PLATED SMOOTH PLATE (TOP VERSION)



- Gas griddle (70 cm top version) with smooth mirror-polished brushed chrome-plated plate recommended for cooking delicate products.
- Horizontal cooking plate (12 cm thick).
- One temperature control.
- Power: 6 kW.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- Scraper included.
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- Stainless steel control panel and side panels.
- Module coupling system with external side joints.
- Appliances intended for direct cooking.
- Cooking plate hermetically sealed to the worktop.
- Heating through stainless steel armoured heating elements.
- \bullet Operating thermostatic valve with temperature control ranging between 70°C and 310°C.
- Grooving with a cap and removable drawer for collecting grease and liquids.
- Removable splashback on 3 sides integrated into the worktop.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Plastic feet (H=51 mm).



TECHNICAL DATA

TOTAL POWER	6 kW	ELECTRIC POWER	6 kW
FREQUENCY	50/60 Hz	VOLTAGE	220-240 ~ V
TEMPERATURE RANGE	50÷320 °C	MINIMUM POWER CABLE CROSS-SECTION	3 x 4 n° - mm²
COOKING SURFACE	69,6x56,4 cm	ELECTRIC CABLE TYPE	H07 RN-F
PLATE TYPE	Chrome-plated - smooth	HEATING ZONES	n° 2
ELECTRICAL CONNECTION HEIGHT (H)	0 mm	ELECTRICAL CONNECTION HEIGHT (X)	647 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-445 mm	FOOT HEIGHT	51 mm
IPX RATING	4	WIDTH	70 cm
DEPTH	60 cm	HEIGHT	30 cm
PACKAGE WIDTH	77 cm	PACKAGE DEPTH	72 cm
PACKAGE HEIGHT	54 cm	NET WEIGHT	57 kg
GROSS WEIGHT	61,5 kg	VOLUME	0,30 m³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	2400.0 W
SENSIBLE HEAT RELEASE	1980.0 W	STEAM RELEASE	3528.0 g/h

ACCESSORIES

120590 PAIR OF JOINTS FOR GRIDDLES 120595 GRIDDLE-CLEANING SCRAPER 120597 SCRAPER - SPARE BLADE KIT (10 PCS) 120669 SPLASHBACK L=700MM FOR GRIDDLE



INSTALLATION SCHEMES

775 - REG FT E/6/ - FT E/ INGRESSO CAVO ELETTRICO ELECTRIC CABLE INLET INGRESSO CAVO ELETTRICO ELECTRIC CABLE INLET 650 44 50 58 **†**6† 5415.679.00 182 LL 53 89 350 - 700 EQUIPOTENZIALE -EQUIPOTENTIAL Data scarque | Print da le 16.04.14 52 ÷ 32 944 23 89 350 - 700 EQUIPOTENZIALE EQUIPOTENTIAL INGRESSO CAVO ELETTRICO ELECTRIC CABLE INLET 330 28 INGRESSO CAVO ELETTRICO ELECTRIC CABLE INLET 4 900 300 - FIX