
126025

FTL70E/2

ELECTRIC GRIDDLE WITH SMOOTH PLATE AND TEMPERATURE CONTROL (TOP VERSION)



- Electric griddle (70 cm top version) with a smooth steel plate.
- Horizontal cooking plate (12 cm thick).
- One temperature control.
- Stainless steel control panel and side panels.
- Module coupling system with external side joints.
- Appliances intended for direct cooking.
- Cooking plate hermetically sealed to the worktop.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 310°C.
- Grooving with a cap and removable drawer for collecting grease and liquids.
- Removable splashback on 3 sides integrated into the worktop.
- Fitted with a safety thermostat that triggers in case of abnormal operation.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Technical compartment to facilitate connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	6 kW	ELECTRIC POWER	6 kW
FREQUENCY	50/60 Hz	VOLTAGE	220-240 ~ V
TEMPERATURE RANGE	50÷320 °C	MINIMUM POWER CABLE CROSS-SECTION	3 x 4 n° - mm ²
COOKING SURFACE	69,6x56,4 cm	ELECTRIC CABLE TYPE	H07 RN-F
PLATE TYPE	Smooth	HEATING ZONES	n° 2
ELECTRICAL CONNECTION HEIGHT (H)	0 mm	ELECTRICAL CONNECTION HEIGHT (X)	647 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-494 mm	FOOT HEIGHT	25 mm
FOOT ADJUSTMENT	25/35 mm	IPX RATING	4
WIDTH	70 cm	DEPTH	65 cm
HEIGHT	28 cm	PACKAGE WIDTH	76,0 cm
PACKAGE DEPTH	71,0 cm	PACKAGE HEIGHT	53,0 cm
NET WEIGHT	58,9000 kg	GROSS WEIGHT	66,4000 kg
VOLUME	0,2900 m ³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	2400.0 W	SENSIBLE HEAT RELEASE	1980.0 W
STEAM RELEASE	3528.0 g/h		

ACCESSORIES

120590	PAIR OF JOINTS FOR GRIDDLES
120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)

INSTALLATION SCHEMES



Barra (mm) (mm dia.)	16.04.14	Condotti (mm)	5415.679.00	Foglio (Sheet)	1	Modello (Models)	FT-E/6/ - FT-E/
----------------------	----------	---------------	-------------	----------------	---	------------------	-----------------