# **DROP-IN**



133006

## DPCG70G



#### • 4-burner gas drop-in (70 x 60 x 30.7 cm).

• Drop-ins are appliances inserted into worktops of different non-flammable materials. Modules can rest on the worktop or be installed flush the worktop.

**4-BURNER GAS BOILING TOP (DROP-IN VERSION)** 

• Deep drawn worktop featuring rounded corners to prevent overflows and ensure enhanced hygiene and easy cleaning.

 $\bullet$  Cast-iron enamelled burners fixed to the worktop with a single ring (3.3 kW and 5.2 kW).

- Brass flame spreader.
- Burner activation using a piezoelectric device.
- Safety thermocouple.
- Valved gas cock.

• Enamelled cast iron pan support grid to resist acids, acids, alkalis and flames.

- Stainless steel control panel.
- AISI 304 stainless steel worktop with Scotch Brite finish.

• The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.

• Unless specified otherwise, the models in the price list are tested with G20 natural gas nozzles and include a set of nozzles for conversion to G30/G31 LPG gas or vice versa, based on customer order.

### **TECHNICAL DATA**

TOTAL POWER	17 kW	GAS POWER	17 kW
OPEN BURNER POWER	2X3,3+2X5,2 n°- kW	BOILING TOP POWER	17 kW
NUMBER OF BURNERS	n° 4	BOILING PAN SUPPORT	RAAF enamelled cast iron
CE GAS CERTIFICATE NUMBER	CE-0085BO0091	GAS CONNECTION DIAMETER	1/2"G EN10226-1
WIDTH	70 cm	DEPTH	60 cm
HEIGHT	30,7 cm	PACKAGE WIDTH	76,0 cm
PACKAGE DEPTH	71,0 cm	PACKAGE HEIGHT	53,0 cm
NET WEIGHT	21 kg	GROSS WEIGHT	28 kg
VOLUME	0,29 m <sup>3</sup>	HARMONISED CODE	84198180
LPG CONSUMPTION	1.34 m³/h		

#### ACCESSORIES

120655 PAN SUPPORT REDUCER

### INSTALLATION SCHEMES

