
216015

SEC40/0CB

ELECTRIC LIGHT SALAMANDER WITH MOVABLE TOP (AISI 430 SEC 40X45X50 CM)



- Light SEC40/0CB electric salamander (40 cm) with movable plate.
- 1 cooking zone 40x35 cm.
- A salamander is a versatile appliance used for cooking au gratin, keeping ready-to-serve dishes warm, finishing baked dishes like lasagna and flans, as well as grilling and finishing meats such as hamburgers, steaks, sausages, and cutlets.
- AISI430 stainless steel structure open on 3 sides.
- Upper movable plate with 90° corners sliding on guides.
- Heating through Incoloy armoured heating elements on the upper movable plate.
- Heating elements can be sloped to facilitate maintenance.
- Temperature control via energy regulator.
- Heat-resistant, duroplast handle.
- Removable chrome-plated steel cooking grid and AISI304 stainless steel grease collection container with heat-resistant handle.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Wall installation brackets (optional)

TECHNICAL DATA

TOTAL POWER	2 kW	ELECTRIC POWER	2 kW
FREQUENCY	50/60 Hz	VOLTAGE	220-240 ~ V
HEATING PLATES	n° 1	MINIMUM POWER CABLE CROSS-SECTION	3 x 1,5 n° - mm ²
COOKING SURFACE	40x35 cm	ELECTRIC CABLE TYPE	H07 RN-F
HEATING ZONES	n° 1	ELECTRICAL CONNECTION HEIGHT (Y)	0 mm
IPX RATING	3	WIDTH	40 cm
DEPTH	45 cm	HEIGHT	50 cm
PACKAGE WIDTH	51 cm	PACKAGE DEPTH	61 cm
PACKAGE HEIGHT	72 cm	NET WEIGHT	32,9000 kg
GROSS WEIGHT	39 kg	VOLUME	0,22 m ³
HARMONISED CODE	84198180		

ACCESSORIES

9003 PAIR OF WALL BRACKETS FOR SALAMANDERS (QSE-SE)

INSTALLATION SCHEMES

537
496
378
507
92
37
34
AL
600 (SEC60 /)
33
33
15-25
100
37
254
104
354
542 (SEC60)
342 (SEC40)
53

Schema di foratura parete in calcestruzzo per fissaggio staffe
 Diagram for drilling cement walls for the fastening of brackets
 Schema für Betonwandbohrungen zur Befestigung der Wandhalterungen
 Schéma de perçage de la paroi en béton pour fixer les étriers
 Esquema de perforación de la pared de hormigón para fijación soportes

AL
AL2
EQUIPOTENZIALE
EQUIPOTENTIAL
T1
T2
M

MODEL: []
 CODE: []
 SH: []
 IPX: []
 CE
 EQUIPOTENZIALE EQUIPOTENTIAL

AL | Entrata cavo elettrico | Power supply cable inlet | Netzkabeleingang | Entrée cable électrique | Entrada cable eléctrico.
 AL2 | Alternativo | Alternative | Alternative | Alternative | Alternativa

Data stamp / F. n. data: 26.02.20
 Foglio / Sheet: 1/1
 Formato / Format: A3
 Scala / Scale: 0.150
 Modello / Model: SEC40_ / SEC60_
 Codice / Code: 5416.291.00