

---

**216017**

SEC60/4CB

**ELECTRIC LIGHT SALAMANDER WITH MOVABLE TOP (AISI 430 SEC 60X45X50 CM)**

---



- Light SEC60/4 electric salamander (60 cm) with movable plate.
- 2 independent cooking zones for an overall surface of 60x35 cm, compatible with GN1/1.
- A salamander is a versatile appliance used for cooking au gratin, keeping ready-to-serve dishes warm, finishing baked dishes like lasagna and flans, as well as grilling and finishing meats such as hamburgers, steaks, sausages, and cutlets.
- AISI430 stainless steel structure open on 3 sides.
- Upper movable plate with 90° corners sliding on guides.
- Heating through Incoloy armoured heating elements on the upper movable plate.
- Heating elements can be sloped to facilitate maintenance.
- Temperature control via energy regulator.
- Heat-resistant, duroplast handle.
- Removable chrome-plated steel cooking grid and AISI304 stainless steel grease collection container with heat-resistant handle.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Wall installation brackets (optional)

---

**TECHNICAL DATA**

TOTAL POWER	4 kW	ELECTRIC POWER	4 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 2N ~ V
HEATING PLATES	n° 1	MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm <sup>2</sup>
COOKING SURFACE	60x35 cm	ELECTRIC CABLE TYPE	H07 RN-F
HEATING ZONES	n° 2	ELECTRICAL CONNECTION HEIGHT (H)	23 mm
ELECTRICAL CONNECTION HEIGHT (X)	380 mm	ELECTRICAL CONNECTION HEIGHT (Y)	0 mm
IPX RATING	3	WIDTH	60 cm
DEPTH	45 cm	HEIGHT	50 cm
PACKAGE WIDTH	68,0 cm	PACKAGE DEPTH	56,0 cm
PACKAGE HEIGHT	72,0 cm	NET WEIGHT	47,0000 kg
GROSS WEIGHT	54,0000 kg	VOLUME	0,2700 m <sup>3</sup>
HARMONISED CODE	84198180		

---

**ACCESSORIES**

9003 PAIR OF WALL BRACKETS FOR SALAMANDERS (QSE-SE)

INSTALLATION SCHEMES

537  
496  
378  
507  
37  
34  
AL  
106-251  
537  
378  
507  
92  
37  
34  
AL  
106-251

600 (SEC60/ )  
33  
33  
15-25  
100  
37  
254  
104

400 (SEC40/ )  
33

354  
53  
542 (SEC60)  
342 (SEC40)

Schema di foratura parete in calcestruzzo per fissaggio staffe  
 Diagram for drilling cement walls for the fastening of brackets  
 Schema für Betonwandbohrungen zur Befestigung der Wandhalterungen  
 Schéma de perçage de la paroi en béton pour fixer les étriers  
 Esquema de perforación de la pared de hormigón para fijación soportes

AL | Entrata cavo elettrico | Power supply cable inlet | Netzkabeleingang | Entrée cable électrique | Entrada cable eléctrico.  
 AL2 | Alternativo | Alternative | Alternative | Alternative | Alternativa

CE mark label: MODEL, CODE, SH, IPX, CE, EQUIPOTENZIALE EQUIPOTENTIAL

1/1 A3 0.150  
 Foglio | Sheet | Folha | Blatt | 1/1  
 Formato | Format | Formato | Format | A3  
 Data stampa | Print date | Data de impressão | Druckdatum | 26.02.20  
 Modello | Model | Modelo | Modell | SEC40\_ / SEC60\_  
 Codice | Code | Código | Code | 5416.291.00