

**216037**

QSE60/0CB

**ULTRA-RAPID ELECTRIC SALAMANDER WITH  
MOVABLE TOP (QSE)**



- QSE60/0CB ultrarapid electric salamander (60 cm) with movable plate.
- 2 independent cooking zones for an overall surface of 60x35 cm, compatible with GN1/1.
- A salamander is a versatile appliance used for cooking au gratin, keeping ready-to-serve dishes warm, finishing baked dishes like lasagna and flans, as well as grilling and finishing meats such as hamburgers, steaks, sausages, and cutlets.
- AISI304 stainless steel structure open on 3 sides.
- Upper movable plate with rounded corners sliding on guides.
- Ultra-rapid infrared heating elements installed on the movable upper plate, protected by a glass ceramic plate.
- On first startup, the set operating temperature is reached in just 20 seconds. For subsequent uses, it takes just 5 seconds, leading to substantial energy savings.
- Aluminium handle with heat-resistant spacers.
- Knob for adjusting the cooking time from 0 to 99 minutes, displayed on the digital screen.
- START and STOP touch buttons.
- Air intakes on the moveable upper plate to expel heat and fumes.
- Removable chrome-plated steel cooking grid and AISI304 stainless steel grease collection container with heat-resistant handle.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Wall installation brackets (optional)

---

**TECHNICAL DATA**

TOTAL POWER	4 kW	ELECTRIC POWER	4 kW
FREQUENCY	50/60 Hz	VOLTAGE	220-240 ~ V
HEATING PLATES	n° 1	MINIMUM POWER CABLE CROSS-SECTION	3 x 2,5 n° - mm <sup>2</sup>
COOKING SURFACE	60x35 cm	TIMER	0-99 min
ELECTRIC CABLE TYPE	H07 RN-F	HEATING ZONES	n° 2
ELECTRICAL CONNECTION HEIGHT (H)	24 mm	ELECTRICAL CONNECTION HEIGHT (X)	380 mm
ELECTRICAL CONNECTION HEIGHT (Y)	0 mm	FOOT HEIGHT	31 mm
IPX RATING	3	WIDTH	60 cm
DEPTH	54,8 cm	HEIGHT	50 cm
PACKAGE WIDTH	71 cm	PACKAGE DEPTH	60 cm
PACKAGE HEIGHT	72 cm	NET WEIGHT	52 kg
GROSS WEIGHT	61 kg	VOLUME	0,31 m <sup>3</sup>
HARMONISED CODE	84198180		

---

**ACCESSORIES**

9003 PAIR OF WALL BRACKETS FOR SALAMANDERS (QSE-SE)

INSTALLATION SCHEMES

**RAPID SALAMANDER SE\_**

600 (SE60 )  
400 (SE40 )  
800 (SE80 )

**ULTRA RAPID SALAMANDER QSE\_**

600 (QSE\_60)  
400 (QSE\_40)

**Schema di foratura parete in calcestruzzo per fissaggio staffe**  
**Diagram for drilling cement walls for the fastening of brackets**  
**Schema für Betonwandbohrungen zur Befestigung der Wandhalterungen**  
**Schema de perçage de la paroi en béton pour fixer les étriers**  
**Esquema de perforación de la pared de hormigón para fijación soportes**

Al | Entrata cavo elettrico | Power supply cable inlet | Netzkabeleingang | Entrée cable électrique | Entrada cable eléctrico.

AL2 | Alternativo | Alternative | Alternative | Alternative | Alternativa

Model | Modèle | Modell | Modelo

Page | Sheet | Folha | Hoja | Pagina | Blatt

Scale | Scala | Maßstab

1/1 A3 0.150 SE\_40\_ | SE60\_ | SE80\_ | QSE\_40 | QSE\_60

Date | Data | Datum | Fecha

26.02.20

Order Code | Codice | Code

5415.693.01