
216042

SE60/0CB

CLASSIC ELECTRIC SALAMANDER WITH MOVABLE TOP (SE)



- Classic SE60/0CB electric salamander (60 cm) with movable plate.
- 2 independent cooking zones for an overall surface of 60x35 cm, compatible with GN1/1.
- A salamander is a versatile appliance used for cooking au gratin, keeping ready-to-serve dishes warm, finishing baked dishes like lasagna and flans, as well as grilling and finishing meats such as hamburgers, steaks, sausages, and cutlets.
- AISI304 stainless steel structure open on 3 sides.
- Upper movable plate with rounded corners sliding on guides.
- Heating through Incoloy armoured heating elements on the upper movable plate.
- Heating elements can be sloped to facilitate maintenance.
- Temperature control via energy regulator.
- Aluminium handle with heat-resistant spacers.
- Removable chrome-plated steel cooking grid and AISI304 stainless steel grease collection container with heat-resistant handle.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Wall installation brackets (optional)

TECHNICAL DATA

TOTAL POWER	4 kW	ELECTRIC POWER	4 kW
FREQUENCY	50/60 Hz	VOLTAGE	220-240 ~ V
HEATING PLATES	n° 1	MINIMUM POWER CABLE CROSS-SECTION	3 x 2,5 n° - mm ²
COOKING SURFACE	60x35 cm	ELECTRIC CABLE TYPE	H07 RN-F
HEATING ZONES	n° 2	ELECTRICAL CONNECTION HEIGHT (H)	23 mm
ELECTRICAL CONNECTION HEIGHT (X)	380 mm	ELECTRICAL CONNECTION HEIGHT (Y)	0 mm
IPX RATING	3	WIDTH	60 cm
DEPTH	54,8 cm	HEIGHT	50 cm
PACKAGE WIDTH	71 cm	PACKAGE DEPTH	61 cm
PACKAGE HEIGHT	71 cm	NET WEIGHT	52,4 kg
GROSS WEIGHT	60,4 kg	VOLUME	0,31 m ³
HARMONISED CODE	84198180		

ACCESSORIES

9003 PAIR OF WALL BRACKETS FOR SALAMANDERS (QSE-SE)

INSTALLATION SCHEMES

RAPID SALAMANDER SE_

600 (SE60)
400 (SE40)
800 (SE80)

ULTRA RAPID SALAMANDER QSE_

600 (QSE_60)
400 (QSE_40)

Schema di foratura parete in calcestruzzo per fissaggio staffe
Diagram for drilling cement walls for the fastening of brackets
Schema für Betonwandbohrungen zur Befestigung der Wandhalterungen
Schema de perçage de la paroi en béton pour fixer les étriers
Esquema de perforación de la pared de hormigón para fijación soportes

Modello | Modello: **A3**

Formato | Formato: **A3**

Scale | Scala: **1/1**

Foglio | Sheet: **1/1**

Data stampa | Print date: **26.02.20**

Forma | Model: **SE_40_ | SE60_ | QSE_40 | QSE_60**

Colori | Colors: **5415.693.01**

AL | Entrata cavo elettrico | Power supply cable inlet | Netzkabeleingang | Entrée cable électrique | Entrada cable eléctrico.

AL2 | Alternativo | Alternative | Alternative | Alternative | Alternativa