


313006

PP8G9

GAS SOLID BOILING TOP (TOP VERSION)



- Gas solid top, top version (80 cm).
- Non-deformable cast iron plate (1 cm thick).
- 11 kW cast iron central burner to reach a temperature of 500°C at the plate centre, with pilot burner and safety thermocouple.
- Valved gas cock.
- Piezoelectric ignition.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.



TECHNICAL DATA

TOTAL POWER	11 kW	GAS POWER	11 kW
BOILING TOP POWER	11 kW	GAS PLATE POWER	1x11 n°- kW
NATURAL GAS CONSUMPTION	1,16 m³/h	ELECTRIC PLATE DIMENSIONS	76,6x68,3 cm
NUMBER OF BURNERS	n° 1 (plate)	PLATE TYPE	Cast iron
HEATING ZONES	n° 1	CE GAS CERTIFICATE NUMBER	CE-0085BO0092
GAS CONNECTION DIAMETER	1/2" G EN10226-1	GAS CONNECTION HEIGHT (H)	35 mm
GAS CONNECTION HEIGHT (X)	766 mm	GAS CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	15 mm	FOOT ADJUSTMENT	15/25 mm
WIDTH	80 cm	DEPTH	90 cm
HEIGHT	28 cm	PACKAGE WIDTH	86,0 cm
PACKAGE DEPTH	100,0 cm	PACKAGE HEIGHT	55 cm
NET WEIGHT	90 kg	GROSS WEIGHT	111 kg
VOLUME	0,47 m³	HARMONISED CODE	84198180
LPG CONSUMPTION	0.87 m³/h		

ACCESSORIES

- 399516 ADJUSTABLE WATER TAP
399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 || الصورة رقم ١ - 5415.618.00

⚡ SOLO VERSIONI CON FORNO ELETTRICO O VENTILATO | ONLY MODELS WITH ELECTRIC OVEN OR FAN ASSISTED
نماذج فقط مع فرن كهربائي أو بمساعدة مروحة