

313070

CP4FG9

**GN1/1 FREESTANDING GAS PASTA COOKER 40L
ON CLOSED CABINET - BASKETS NOT INCLUDED**



- Freestanding GN1/1 gas pasta cooker 40 L on a closed cabinet (40 cm).
- Power: 15 kW.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Pasta cookers are used to boil rice, vegetables, meat and other products.
- Deep drawn worktop with a seamlessly welded deep drawn pressed cooking tank, featuring rounded corners, overflow-proof tank and large foam expansion area.
- AISI 316 stainless steel tank, outlet pipe drainpipe, and false bottom for long-lasting resistance against salt corrosion.
- Heating through a 15 kW tubular burner outside the tank.
- Valved gas cock.
- Piezoelectric ignition.
- Pilot burner and safety thermocouple.
- Safety thermostat to protect the tank against ignition without water or excessive evaporation.
- Water inlet on the worktop rear. at the rear of the worktop.
- Overflow for draining starch in the front part of the tank.
- Bottom drain.
- Technical compartment for easy connection to the gas network.
- Baskets not included.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.


TECHNICAL DATA

TOTAL POWER	15 kW	GAS POWER	15 kW
TANK CAPACITY	40lt	LOADING WATER	Water inlet on the worktop
NATURAL GAS CONSUMPTION	1,58 m³/h	TANK DIMENSIONS	51x30,5x31 cm
TANK TYPE	AISI 316	CE GAS CERTIFICATE NUMBER	CE-0085BO0097
WATER CONNECTION POSITION	Bottom	WATER DRAIN POSITION	Bottom
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	0 mm
GAS CONNECTION HEIGHT (X)	367 mm	GAS CONNECTION HEIGHT (Y)	-671 mm
WATER CONNECTION DIAMETER	1/2"	WATER CONNECTION HEIGHT (H)	0 mm
WATER CONNECTION HEIGHT (X)	120 mm	WATER CONNECTION HEIGHT (Y)	-620 mm
DRAIN DIAMETER	1"	DRAIN CONNECTION HEIGHT (H)	0 mm
DRAIN CONNECTION HEIGHT (X)	295 mm	DRAIN CONNECTION HEIGHT (Y)	-620 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
WIDTH	40 cm	DEPTH	90 cm
HEIGHT	90 cm	PACKAGE WIDTH	46 cm
PACKAGE DEPTH	100 cm	PACKAGE HEIGHT	115 cm
NET WEIGHT	62 kg	GROSS WEIGHT	72 kg
VOLUME	0,53 m³	HARMONISED CODE	84198180
LPG CONSUMPTION	1.18 m³/h	LATENT HEAT RELEASE	4500.0 W
SENSIBLE HEAT RELEASE	1500.0 W	STEAM RELEASE	6615.0 g/h

ACCESSORIES

120650	LID (GN1/1)
319009	REAR COVERING PANEL FOR CABINET (L=40CM)
399504	PASTA COOKER BASKET (3 X GN1/3) - DIM. CM (29X16X20H)
399505	PASTA COOKER BASKET (1 X GN1/3 + 2 X GN2/6) - DIM. CM (29X16X20H)
399506	PASTA COOKER BASKET (2 X GN1/3 + 2 X GN1/6) - DIM. CM (29X16X20H) (14X14X20H)
399507	PASTA COOKER BASKET (1 X GN1/3 + 4 X GN1/6) - DIM. CM (29X16X20H) (14X14X20H)
399508	PASTA COOKER BASKET (1 X GN1/3 + 1 X GN2/3) - DIM. CM (29X16X20H) (29X29X20H)
399548	PASTA COOKER BASKET (6 X GN1/6) - DIM. CM (14X14X20H)
399553	PASTA COOKER BASKET (2 X GN1/2) - DIM. CM (29X24X20H)
399572	PASTA COOKER BASKET (GN1/1) - DIM. CM (49X29X20H)
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



5415.640.01