## MOSAICO90



313159

PCGM12FG9/1

## FREESTANDING 3-BURNER GAS BOILING TOP WITH CAST IRON GRIDS ON OPEN CABINET



- Freestanding 3-burner gas boiling top on an open cabinet (120x45 cm) (SUPER version).
- High-efficiency cast iron burners and flame spreaders with a double ring (9.0 kW).
- Mosaico90 is a special line of modular units, 45 cm deep, which combine

perfectly with the Tecno90 range to create compact cooking islands designed to make the best use of space.

- AISI 304 stainless steel worktop (20/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel and side panels.
- Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- $\bullet$  Enamelled cast iron pan support grid to resist acids, acids, alkalis and flames.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is included, should conversion on site be necessary.



			CA			

TOTAL POWER	27 kW	GAS POWER	27 kW
OPEN BURNER POWER	3X9 n°- kW	BOILING TOP POWER	27 kW
NATURAL GAS CONSUMPTION	2,85 m³/h	LPG CONSUMPTION	2.13 m³/h
CABINET DIMENSIONS	113X34X39,5 cm	NUMBER OF BURNERS	n° 3
BOILING PAN SUPPORT	RAAF enamelled cast iron	CE GAS CERTIFICATE NUMBER	CE-0085CR0045
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	486 mm
GAS CONNECTION HEIGHT (X)	122 mm	GAS CONNECTION HEIGHT (Y)	-45 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
WIDTH	120 cm	DEPTH	45 cm
HEIGHT	90 cm	PACKAGE WIDTH	127 cm
PACKAGE DEPTH	53 cm	PACKAGE HEIGHT	115 cm
NET WEIGHT	72 kg	GROSS WEIGHT	82 kg
VOLUME	0,77 m³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	3240.0 W	SENSIBLE HEAT RELEASE	8100.0 W
STEAM RELEASE	4752.0 g/h		

## **ACCESSORIES**

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90



## **INSTALLATION SCHEMES**

