
313176

B8FXGN9

FREESTANDING TILTING GAS BRATT PAN 80L WITH AN AISI 304 STAINLESS STEEL TANK ON CLOSED CABINET



- Freestanding tilting gas bratt pan 80 L (80 cm). Manual tank lifting.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- The braising pan bratt pan is intended to braise and prepare stews, sauces, risottos, pan-fried vegetables and cooking with minimal liquid. Use as a fryer is not allowed.
- AISI 304 tilting tank with a 12 mm bottom and 2 mm walls.
- Heating through a multi-branch stainless steel tubular burner.
- Valve with thermopile 0-pilot burner-BURNER.
- Thermostatic control 0-50-300°C.
- Piezoelectric ignition.
- Safety thermocouple.
- Micro safety switch on the lifting mechanism: when the tank is lifted the burner switches off, leaving the pilot burner active.
- AISI 304 stainless steel spring-balance lid with integrated handle and hinge.
- Water filling control on the front panel.
- Water inlet fixed on the rear of the worktop, outside the tank.
- AISI 304 height-adjustable feet (133/195 mm).
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECHNICAL DATA

TOTAL POWER	20 kW	GAS POWER	20 kW
TEMPERATURE RANGE	100÷300 °C	TANK CAPACITY	80lt
NATURAL GAS CONSUMPTION	2,11 m³/h	TANK DIMENSIONS	69,8x56,4x20 cm
TANK BOTTOM THICKNESS	12 mm	DRAINING THE TANK	Manual tipping
TANK TYPE	AISI 304	CE GAS CERTIFICATE NUMBER	CE-0085CT0178
WATER CONNECTION POSITION	Bottom	ELECTRICAL CONNECTION HEIGHT (H)	0 mm
ELECTRICAL CONNECTION HEIGHT (X)	87 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-400 mm
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	0 mm
GAS CONNECTION HEIGHT (X)	87 mm	GAS CONNECTION HEIGHT (Y)	-594 mm
WATER CONNECTION DIAMETER	0,472441"	WATER CONNECTION HEIGHT (H)	0 mm
WATER CONNECTION HEIGHT (X)	87 mm	WATER CONNECTION HEIGHT (Y)	-515 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
WIDTH	80 cm	DEPTH	90 cm
HEIGHT	90 cm	PACKAGE WIDTH	107,0 cm
PACKAGE DEPTH	87,0 cm	PACKAGE HEIGHT	117 cm
NET WEIGHT	159,4 kg	GROSS WEIGHT	183 kg
VOLUME	1,08 m³	HARMONISED CODE	84198180
LPG CONSUMPTION	1.58 m³/h		

ACCESSORIES

INSTALLATION SCHEMES

6 FIGURE E DETTAGLI

6.1 PIANTA ALLACCIAMENTO B8

LEGENDA:			
G	Attacco gas (ISO 7-1)	G	Attacco gas (ISO 7-1)
B	Allacciamento acqua	B	Allacciamento acqua
		E	Allacciamento elettrico
		Q	Morsetto equipotenziale

