

313208

GR8FG9T

FREESTANDING LAVA STONE GAS GRILL TOP ON OPEN CABINET



- Freestanding gas lava stone grill on an open cabinet (80 cm).
- Power: 2x10 kW.
- 2 independent cooking zones.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Differentiated perforated burner for enhanced heat distribution, easily removable for cleaning.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner unit protected against dirt.
- Cooking surface with interchangeable grids and rear handle. An AISI304 stainless steel grid (15/10 thick) with an S-profile is included as standard to prevent any flames from the lava stone burning the products. Accessories include a porcelain-coated cast-iron grid grill with double-sided modules, allowing you to cook meat on one side and fish and vegetables on the other. Additionally, an AISI 304 stainless steel rod grid grill is available.
- Grills comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- Grills are adjustable to 2 positions with lifting rods spaced away from heat sources. They are also removable for cleaning.
- Removable lava stone basket.
- Removable splashback on 3 sides included.
- Grooving Basin and drawer for collecting grease and liquids. Every cooking area is equipped with a removable drawer with a cup-like handle. an ergonomic drawer with a removable cup-like handle.
- Dust collection drawer for each cooking area zone, removable from the control panel.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECHNICAL DATA

TOTAL POWER	20 kW	GAS POWER	20 kW
NATURAL GAS CONSUMPTION	2,12 m ³ /h	CABINET DIMENSIONS	73x57,4x39,5 cm
COOKING SURFACE	2x(62x36) cm	GRID TYPE	With S profile
CE GAS CERTIFICATE NUMBER	CE-0085BO0098	GAS CONNECTION DIAMETER	1/2"G EN10226-1
GAS CONNECTION HEIGHT (H)	484 mm	GAS CONNECTION HEIGHT (X)	766 mm
GAS CONNECTION HEIGHT (Y)	-75 mm	FOOT HEIGHT	133 mm
FOOT ADJUSTMENT	133/195 mm	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	86 cm	PACKAGE DEPTH	101 cm
PACKAGE HEIGHT	112 cm	NET WEIGHT	108 kg
GROSS WEIGHT	125 kg	VOLUME	0,97 m ³
HARMONISED CODE	84198180	LPG CONSUMPTION	1.58 m ³ /h
LATENT HEAT RELEASE	4000.0 W	SENSIBLE HEAT RELEASE	14400.0 W
STEAM RELEASE	5880.0 g/h		

ACCESSORIES

- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 399583 TECNO90 ROD MODULE GRID (1/2) FOR LAVA STONE
- 399584 TECNO90 CAST IRON MODULE GRID (1/2) FOR LAVA STONE

