


313214

PPF8GG9

**GAS SOLID TOP BOILING TOP ON GN2/1 GAS  
STATIC OVEN WITH 1 GRID**



IMMAGINE DA DEFINIRE



- Solid top gas cooker on a GN 2/1 gas static oven (80 cm).
- Non-deformable cast iron plate (1 cm thick).
- 11 kW cast iron central burner to reach a temperature of 500°C at the plate centre, with pilot burner and safety thermocouple.
- Valved gas cock.
- Piezoelectric ignition.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).

>> GN 2/1 GAS STATIC OVEN

>> AISI 304 stainless steel oven door.

>> Stainless steel cooking chamber and long-lasting steel mesh and glass fibre gasket resistant to high temperatures.

>> Equipped with thermostatic valve, 150-290°C regulation.

>> Pilot burner ignition with a thermocouple through a piezoelectric device.

>> Stainless steel removable side tray racks.

>> 1 grid included.

• AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.

• AISI 304 stainless steel control panel and side panels.

• Technical compartment to make easy the connection to the gas network.

• The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.

• The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

## TECHNICAL DATA

TOTAL POWER	18 kW	GAS POWER	18 kW
OVEN POWER	7 kW	BOILING TOP POWER	11 kW
GAS PLATE POWER	1x11 n°- kW	TRAY CAPACITY	n° 4xGN2/1
NATURAL GAS CONSUMPTION	1,9 m³/h	LPG CONSUMPTION	1.42 m³/h
COOKING CHAMBER DIMENSIONS	57,5x65x30 cm	OVEN DIMENSIONS	GN2/1
ELECTRIC PLATE DIMENSIONS	76,6x68,3 cm	GUIDES	n° 4
NUMBER OF BURNERS	n° 1 (plate)	VERTICAL DISTANCE BETWEEN TRAYS	6 cm
OVEN TEMPERATURE RANGE	150÷290 °C	OVEN TYPE	Static
PLATE TYPE	Cast iron	HEATING ZONES	n° 1
CE GAS CERTIFICATE NUMBER	CE-0085BO0092	ELECTRICAL CONNECTION HEIGHT (H)	25 mm
ELECTRICAL CONNECTION HEIGHT (X)	729 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-74 mm
GAS CONNECTION DIAMETER	3/4"G EN10226-1	GAS CONNECTION HEIGHT (H)	484 mm
GAS CONNECTION HEIGHT (X)	766 mm	GAS CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	87,0 cm	PACKAGE DEPTH	101,0 cm
PACKAGE HEIGHT	114,0 cm	NET WEIGHT	157,0000 kg
GROSS WEIGHT	179,0000 kg	VOLUME	1 m³
HARMONISED CODE	84198180		

## ACCESSORIES

220590	EXTRA OVEN GRID GN2/1 (53X63CM)
319010	REAR COVERING PANEL FOR CABINET (L=80CM)
319011	REAR COVERING PANEL FOR CABINET (L=120CM)
399569	ADJUSTABLE WATER TAP FOR KITCHENS WITH A FLUE
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)
619012	GN2/1 INOX TRAY

INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 || الصورة رقم ١ - 5415.618.00

⚡ SOLO VERSIONI CON FORNO ELETTRICO O VENTILATO | ONLY MODELS WITH ELECTRIC OVEN OR FAN ASSISTED  
 نمذاج فقط مع فرن كهربائي أو بمساعدة مروحة