

---

**313222**

FTR12G9

**GAS GRIDDLE WITH A 1/3 RIBBED PLATE (TOP VERSION)**

---



- Gas griddle (120), top version, with 2/3 smooth and 1/3 ribbed steel plate.
- The cooking plate recessed and hermetically welded to the worktop allows you to cook large quantities of different foods.
- Heating through 3 2-branch chrome-plated steel burners (8 kW) with 3 independent working zones.
- Operating thermostatic valve
- Height-adjustable (15/25 mm) rubbered plastic feet.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Sloped Inclined cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

## TECHNICAL DATA

TOTAL POWER	24 kW	GAS POWER	24 kW
TEMPERATURE RANGE	60÷300 °C	NATURAL GAS CONSUMPTION	2,55 m³/h
COOKING SURFACE	113x69 cm	PLATE TYPE	1/3 ribbed and 2/3 smooth
HEATING ZONES	n° 3	CE GAS CERTIFICATE NUMBER	CE-0085B00093
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	35 mm
GAS CONNECTION HEIGHT (X)	1166 mm	GAS CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	15 mm	FOOT ADJUSTMENT	15/25 mm
WIDTH	120 cm	DEPTH	90 cm
HEIGHT	28 cm	PACKAGE WIDTH	125 cm
PACKAGE DEPTH	99 cm	PACKAGE HEIGHT	54 cm
NET WEIGHT	175 kg	GROSS WEIGHT	190 kg
VOLUME	0,66 m³	HARMONISED CODE	84198180
LPG CONSUMPTION	1.89 m³/h	LATENT HEAT RELEASE	9600.0 W
SENSIBLE HEAT RELEASE	8400.0 W	STEAM RELEASE	14112.0 g/h

## ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
319002	STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
319009	REAR COVERING PANEL FOR CABINET (L=40CM)
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 || الصورة رقم ١ - 5415.618.00

⚡ SOLO VERSIONI CON FORNO ELETTRICO O VENTILATO | ONLY MODELS WITH ELECTRIC OVEN OR FAN ASSISTED  
 نمذاج فقط مع فرن كهربائي أو بمساعدة مروحة