
313240**FTL4G9****GAS GRIDDLE WITH A SMOOTH PLATE (TOP VERSION)**



- Gas griddle (40 cm), top version with a smooth steel cooking plate. Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through 1 two-branch chrome-plated steel burner (8 kW).
- Valved gas cock with maximum temperature of 390°C.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Sloped Inclined cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECHNICAL DATA

TOTAL POWER	8 kW	GAS POWER	8 kW
NATURAL GAS CONSUMPTION	0,84 m³/h	COOKING SURFACE	34,9x69,8 cm
PLATE TYPE	Smooth	HEATING ZONES	n° 1
CE GAS CERTIFICATE NUMBER	CE-0085BO0093	GAS CONNECTION DIAMETER	1/2"G EN10226-1
GAS CONNECTION HEIGHT (H)	35 mm	GAS CONNECTION HEIGHT (X)	366 mm
GAS CONNECTION HEIGHT (Y)	-75 mm	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	WIDTH	40 cm
DEPTH	90 cm	HEIGHT	28 cm
PACKAGE WIDTH	100,0 cm	PACKAGE DEPTH	46,0 cm
PACKAGE HEIGHT	58,0 cm	NET WEIGHT	58,0000 kg
GROSS WEIGHT	67,0000 kg	VOLUME	0,2600 m³
HARMONISED CODE	84198180	LPG CONSUMPTION	0.63 m³/h
LATENT HEAT RELEASE	3200.0 W	SENSIBLE HEAT RELEASE	2800.0 W
STEAM RELEASE	4704.0 g/h		

ACCESSORIES

- 120595 GRIDDLE-CLEANING SCRAPER
- 120597 SCRAPER - SPARE BLADE KIT (10 PCS)
- 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 || الصورة رقم ١ - 5415.618.00

⚡ SOLO VERSIONI CON FORNO ELETTRICO O VENTILATO | ONLY MODELS WITH ELECTRIC OVEN OR FAN ASSISTED
 نمذاج فقط مع فرن كهربائي أو بمساعدة مروحة