

313250

FTR8FG9

FREESTANDING GAS GRIDDLE WITH 1/3 RIBBED PLATE ON OPEN CABINET



- Freestanding gas griddle with a 2/3 smooth and 1/3 ribbed steel cooking plate on an open cabinet (80 cm).
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through 2 2-branch chrome-plated steel burners (8 kW) with 2 independent working zones.
- Valved gas cock with maximum temperature of 390°C.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Sloped Inclined cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECHNICAL DATA

| | | | |
|---------------------------|------------------------|---------------------------|---------------------------|
| TOTAL POWER | 16 kW | GAS POWER | 16 kW |
| NATURAL GAS CONSUMPTION | 1,69 m ³ /h | CABINET DIMENSIONS | 77x76,1x39,5 cm |
| COOKING SURFACE | 74,9x69,8 cm | PLATE TYPE | 1/3 ribbed and 2/3 smooth |
| HEATING ZONES | n° 2 | CE GAS CERTIFICATE NUMBER | CE-0085B00093 |
| GAS CONNECTION DIAMETER | 1/2"G EN10226-1 | GAS CONNECTION HEIGHT (H) | 484 mm |
| GAS CONNECTION HEIGHT (X) | 766 mm | GAS CONNECTION HEIGHT (Y) | -75 mm |
| FOOT HEIGHT | 133 mm | FOOT ADJUSTMENT | 133/195 mm |
| WIDTH | 80 cm | DEPTH | 90 cm |
| HEIGHT | 90 cm | PACKAGE WIDTH | 86,0 cm |
| PACKAGE DEPTH | 100,0 cm | PACKAGE HEIGHT | 113 cm |
| NET WEIGHT | 118 kg | GROSS WEIGHT | 140,5 kg |
| VOLUME | 0,9900 m ³ | HARMONISED CODE | 84198180 |
| LPG CONSUMPTION | 1.26 m ³ /h | LATENT HEAT RELEASE | 6400.0 W |
| SENSIBLE HEAT RELEASE | 5600.0 W | STEAM RELEASE | 9408.0 g/h |

ACCESSORIES

| | |
|--------|-----------------------------------------------------------------------|
| 120595 | GRIDDLE-CLEANING SCRAPER |
| 120597 | SCRAPER - SPARE BLADE KIT (10 PCS) |
| 319002 | STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90 |
| 319010 | REAR COVERING PANEL FOR CABINET (L=80CM) |
| 399573 | PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM) |

INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 || الصورة رقم ١ - 5415.618.00

⚡ SOLO VERSIONI CON FORNO ELETTRICO O VENTILATO | ONLY MODELS WITH ELECTRIC OVEN OR FAN ASSISTED
 نمذاج فقط مع فرن كهربائي أو بمساعدة مروحة