


313263

PCH4HPG9

2-BURNER HERMETIC GAS BOILING TOP HIGH POWER WITH CAST IRON GRIDS



- 2-burner gas boiling top (40 cm), HIGH POWER version.
- High-efficiency cast-iron burners hermetically fixed to the top and highly durable brass flame spreaders with single ring (10kW) and double ring (11kW).
- Deep drawn worktop to prevent overflows and with rounded corners for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grids to resist acids, alkalis and flames.
- Setup for installing a water tap.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECHNICAL DATA

TOTAL POWER	21 kW	GAS POWER	21 kW
OPEN BURNER POWER	1X10 + 1X11 n°- kW	BOILING TOP POWER	21 kW
NATURAL GAS CONSUMPTION	2,22 m³/h	NUMBER OF BURNERS	n° 2
BOILING PAN SUPPORT	RAAF enamelled cast iron	CE GAS CERTIFICATE NUMBER	CE-0085BQ0326
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	35 mm
GAS CONNECTION HEIGHT (X)	366 mm	GAS CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	15 mm	FOOT ADJUSTMENT	15/25 mm
WIDTH	40 cm	DEPTH	90 cm
HEIGHT	28 cm	PACKAGE WIDTH	101 cm
PACKAGE DEPTH	46 cm	PACKAGE HEIGHT	60 cm
NET WEIGHT	41,0000 kg	GROSS WEIGHT	47 kg
VOLUME	0,27 m³	HARMONISED CODE	84198180
LPG CONSUMPTION	1.65 m³/h	LATENT HEAT RELEASE	2520.0 W
SENSIBLE HEAT RELEASE	6300.0 W	STEAM RELEASE	3696.0 g/h

ACCESSORIES

319067	10KW HERMETIC FLAME SPREADER
399516	ADJUSTABLE WATER TAP
399538	PAN SUPPORT REDUCER
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 || الصورة رقم ١ - 5415.618.00

⚡ SOLO VERSIONI CON FORNO ELETTRICO O VENTILATO | ONLY MODELS WITH ELECTRIC OVEN OR FAN ASSISTED
 نمذاج فقط مع فرن كهربائي أو بمساعدة مروحة