


313265

PCH4FSG9

2-BURNER HERMETIC GAS BOILING TOP SUPER WITH CAST IRON GRIDS FREESTANDING ON OPEN CABINET



- Freestanding 2-burner gas boiling top on an open cabinet (40 cm), SUPER version.
- High-efficiency cast-iron burners hermetically fixed to the top and highly durable brass flame spreaders with single ring (10kW).
- Deep drawn worktop to prevent overflows and with rounded corners for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grids to resist acids, alkalis and flames.
- Setup for installing a water tap.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECHNICAL DATA

TOTAL POWER	20 kW	GAS POWER	20 kW
OPEN BURNER POWER	2X10 n°- kW	BOILING TOP POWER	20 kW
NATURAL GAS CONSUMPTION	2,12 m³/h	CABINET DIMENSIONS	33x76,1x39,5 cm
NUMBER OF BURNERS	n° 2	BOILING PAN SUPPORT	RAAF enamelled cast iron
CE GAS CERTIFICATE NUMBER	CE-0085BQ0326	GAS CONNECTION DIAMETER	1/2"G EN10226-1
GAS CONNECTION HEIGHT (H)	484 mm	GAS CONNECTION HEIGHT (X)	366 mm
GAS CONNECTION HEIGHT (Y)	-75 mm	FOOT HEIGHT	133 mm
FOOT ADJUSTMENT	133/195 mm	WIDTH	40 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	100,0 cm	PACKAGE DEPTH	46,0 cm
PACKAGE HEIGHT	115,0 cm	NET WEIGHT	52,0000 kg
GROSS WEIGHT	64,4 kg	VOLUME	0,5300 m³
HARMONISED CODE	84198180	LPG CONSUMPTION	1.58 m³/h
LATENT HEAT RELEASE	2400.0 W	SENSIBLE HEAT RELEASE	6000.0 W
STEAM RELEASE	3520.0 g/h		

ACCESSORIES

319002	STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
319067	10KW HERMETIC FLAME SPREADER
399516	ADJUSTABLE WATER TAP
399538	PAN SUPPORT REDUCER

INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 || الصورة رقم ١ - 5415.618.00

⚡ SOLO VERSIONI CON FORNO ELETTRICO O VENTILATO | ONLY MODELS WITH ELECTRIC OVEN OR FAN ASSISTED
 نمذاج فقط مع فرن كهربائي أو بمساعدة مروحة