


316003

PC8E9

**ELECTRIC BOILING TOP WITH 4 SQUARED
HERMETIC PLATES (30X30CM - 11.8X11.8IN, TOP
VERSION)**



- Electric boiling top with 4 squared plates (80 cm).
- Deep drawn worktop with rounded corners to avoid overflow and for maximum hygiene and easy cleaning.
- Cast iron squared electric plates (30x30) hermetically fixed to the deep drawn worktop.
- 4 kW power for each plate adjustable to 6 levels.
- Temperature limiter inside the plates to reduce energy consumption.
- Heating and control commands specific for each plate.
- Lights warning when the plates are on.
- Setup for installing a water tap.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the electrical network.



TECHNICAL DATA

TOTAL POWER	16 kW	ELECTRIC POWER	16 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
BOILING TOP POWER	16 kW	COOKING ZONE POWER	4x4 n°- kW
ELECTRIC PLATE DIMENSIONS	30x30 cm	NUMBER OF COOKING ZONES	n° 4
MINIMUM POWER CABLE CROSS-SECTION	5 x 6 n° - mm ²	ELECTRIC CABLE TYPE	H07 RN-F
ELECTRICAL CONNECTION HEIGHT (H)	35 mm	ELECTRICAL CONNECTION HEIGHT (X)	729 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	IPX RATING	4
WIDTH	80 cm	DEPTH	90 cm
HEIGHT	28 cm	PACKAGE WIDTH	86 cm
PACKAGE DEPTH	100 cm	PACKAGE HEIGHT	55 cm
NET WEIGHT	72 kg	GROSS WEIGHT	82,6 kg
VOLUME	0,47 m ³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	1280.0 W	SENSIBLE HEAT RELEASE	3200.0 W
STEAM RELEASE	1888.0 g/h		

ACCESSORIES

- 399516 ADJUSTABLE WATER TAP
- 399532 TOP FRAME FOR 2 PLATES
- 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00