


316007

PP8E9

ELECTRIC SOLID TOP BOILING TOP (TOP VERSION)



- Electric solid top (80 cm) with 4 independent zones.
- Electric solid tops and cookers are suitable for indirect cooking only.
- Overflow-proof worktop with raised and welded edges.
- Non-deformable, molybdenum steel zone (15 mm thick) with prolonged heat retention properties.
- Ultra-rapid infrared heating elements fixed under the zone with a power of 3.5 kW for each independent zone.
- Maximum temperature of 470°C.
- Thermostatic regulation.
- Temperature limiter inside the zones to reduce energy consumption.
- Heating and control commands specific for each zone.
- Safety thermostat.
- Lights warning when the heating zones are active.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the electrical network.



TECHNICAL DATA

TOTAL POWER	14 kW	ELECTRIC POWER	14 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
BOILING TOP POWER	14 kW	COOKING ZONE POWER	4x3,5 n°- kW
ELECTRIC PLATE DIMENSIONS	77x68,4 cm	NUMBER OF COOKING ZONES	n° 4
PLATE TEMPERATURE RANGE	MAX 450 °C	MINIMUM POWER CABLE CROSS-SECTION	5 x 4 n° - mm ²
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Iron and molybdenum
HEATING ZONES	n° 4	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	15 mm	FOOT ADJUSTMENT	15/25 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	28 cm
PACKAGE WIDTH	86,0 cm	PACKAGE DEPTH	100,0 cm
PACKAGE HEIGHT	58 cm	NET WEIGHT	95,5 kg
GROSS WEIGHT	113 kg	VOLUME	0,50 m ³
HARMONISED CODE	84198180		

ACCESSORIES

- 399569 ADJUSTABLE WATER TAP FOR KITCHENS WITH A FLUE
399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00