


316011

PC8FE9

FREESTANDING ELECTRIC BOILING TOP WITH 4 SQUARED HERMETIC PLATES (30X30CM - 11.8X11.8 IN) ON OPEN CABINET



- Freestanding electric boiling top with 4 squared plates on an open cabinet (80 cm).
- Deep drawn worktop with rounded corners to avoid overflow and for maximum hygiene and easy cleaning.
- Cast iron squared electric plates (30x30) hermetically fixed to the deep drawn worktop.
- 4 kW power for each plate adjustable to 6 levels.
- Temperature limiter inside the plates to reduce energy consumption.
- Heating and control commands specific for each plate.
- Lights warning when the plates are ignited.
- Setup for installing a water tap.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the electrical network.



TECHNICAL DATA

TOTAL POWER	16 kW	ELECTRIC POWER	16 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
BOILING TOP POWER	16 kW	COOKING ZONE POWER	4x4 n°- kW
ELECTRIC PLATE DIMENSIONS	30x30 cm	CABINET DIMENSIONS	77x76,1x39,5 cm
NUMBER OF COOKING ZONES	n° 4	MINIMUM POWER CABLE CROSS-SECTION	5 x 6 n° - mm ²
ELECTRIC CABLE TYPE	H07 RN-F	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	86,0 cm	PACKAGE DEPTH	100,0 cm
PACKAGE HEIGHT	112 cm	NET WEIGHT	83 kg
GROSS WEIGHT	102,6 kg	VOLUME	0,96 m ³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	1280.0 W
SENSIBLE HEAT RELEASE	3200.0 W	STEAM RELEASE	1888.0 g/h

ACCESSORIES

- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 319010 REAR COVERING PANEL FOR CABINET (L=80CM)
- 399516 ADJUSTABLE WATER TAP
- 399532 TOP FRAME FOR 2 PLATES
- 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00