


316041

PFC8E9

ELECTRIC GLASS CERAMIC COOKER ON GN2/1 ELECTRIC STATIC OVEN WITH 1 GRID





- Glass ceramic electric cooker (80 cm) with 4 independent zones on a GN 2/1 electric static oven.
- Glass ceramic top (6 mm thick) hermetically sealed to the worktop for maximum hygiene and ease of cleaning.
- \bullet Ultra-rapid infrared heating elements with a power of 3.4 kW for each independent zone.
- Energy regulator 0-6-infinite.
- Temperature limiter to prevent overheating.
- Heating and control commands specific for each zone.
- Lights warning when the heating zones are active.
- Warning lamps on the glass to enhance operator safety by signalling residual heat.
- Setup for installing a water tap.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).

>> GN 2/1 ELECTRIC STATIC OVEN

- >> AISI 304 stainless steel oven door.
- >> Stainless steel cooking chamber and long-lasting steel mesh and glass fibre gasket resistant to high temperatures.
- >> Heating through upper and lower heating elements that can be activated together or separately.
 - >> Thermostatic control 60-270°C.
 - >> Stainless steel removable side tray racks.
 - >> 1 grid included.
- \bullet AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the electrical network.



TECHNICAL DATA			
TOTAL POWER	18,9 kW	ELECTRIC POWER	18,9 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
OVEN POWER	5,3 kW	BOILING TOP POWER	13,6 kW
COOKING ZONE POWER	4x3,4 n°- kW	TRAY CAPACITY	n° 4xGN2/1
COOKING CHAMBER DIMENSIONS	57,5x65x30 cm	OVEN DIMENSIONS	GN2/1
2-ZONE HEATING ELEMENTS	n° 4	GUIDES	n° 4
NUMBER OF COOKING ZONES	n° 4	VERTICAL DISTANCE BETWEEN TRAYS	6 cm
OVEN TEMPERATURE RANGE	60÷270 °C	MINIMUM POWER CABLE CROSS-SECTION	5 x 6 n° - mm²
ELECTRIC CABLE TYPE	H07 RN-F	OVEN TYPE	Static
HEATING ZONES	n° 4	ELECTRICAL CONNECTION HEIGHT (H)	484 mm
ELECTRICAL CONNECTION HEIGHT (X)	729 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	90 cm

PACKAGE DEPTH

STEAM RELEASE

LATENT HEAT RELEASE

NET WEIGHT

VOLUME

101 cm

107 kg

0,98 m³

1512.0 W

2230.2 g/h

ACCESSORIES

PACKAGE WIDTH

PACKAGE HEIGHT

HARMONISED CODE

SENSIBLE HEAT RELEASE

GROSS WEIGHT

220590 EXTRA OVEN GRID GN2/1 (53X63CM)

319010 REAR COVERING PANEL FOR CABINET (L=80CM)

399516 ADJUSTABLE WATER TAP

399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

86 cm

113 cm

127 kg

84198180

3780.0 W

619012 GN2/1 INOX TRAY



INSTALLATION SCHEMES

