


316043

PPF8E9

ELECTRIC SOLID TOP COOKER ON GN2/1 ELECTRIC STATIC OVEN WITH 1 GRID



- Electric solid top cooker (80 cm) with 4 independent zones on a GN 2/1 electric static oven.
- Electric solid tops and cookers are suitable for indirect cooking only.
- Overflow-proof worktop with raised and welded edges.
- Non-deformable, molybdenum steel zone (15 mm thick) with prolonged heat retention properties.
- Ultra-rapid infrared heating elements fixed under the zone with a power of 3.5 kW for each independent zone.
- Maximum temperature of 470°C.
- Thermostatic regulation.
- Temperature limiter inside the zones to reduce energy consumption.
- Heating and control commands specific for each zone.
- Safety thermostat.
 - GN 2/1 ELECTRIC STATIC OVEN
 - >> AISI 304 stainless steel oven door.
 - >> Stainless steel cooking chamber and long-lasting steel mesh and glass fibre gasket resistant to high temperatures.
 - Heating through upper and lower heating elements that can be activated together or separately.
 - Thermostatic control 60-270°C.
 - >> Stainless steel removable side tray racks.
 - >> 1 grid included.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	19,3 kW	ELECTRIC POWER	19,3 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
OVEN POWER	5,3 kW	BOILING TOP POWER	14 kW
COOKING ZONE POWER	4x3,5 n°- kW	TRAY CAPACITY	n° 4xGN2/1
COOKING CHAMBER DIMENSIONS	57,5x65x30 cm	OVEN DIMENSIONS	GN2/1
ELECTRIC PLATE DIMENSIONS	77x68,4 cm	GUIDES	n° 4
NUMBER OF COOKING ZONES	n° 4	VERTICAL DISTANCE BETWEEN TRAYS	6 cm
OVEN TEMPERATURE RANGE	60÷270 °C	PLATE TEMPERATURE RANGE	MAX 450 °C
MINIMUM POWER CABLE CROSS-SECTION	5 x 6 n° - mm ²	ELECTRIC CABLE TYPE	H07 RN-F
OVEN TYPE	Static	PLATE TYPE	Iron and molybdenum
HEATING ZONES	n° 4	ELECTRICAL CONNECTION HEIGHT (H)	484 mm
ELECTRICAL CONNECTION HEIGHT (X)	729 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	86,0 cm	PACKAGE DEPTH	100,0 cm
PACKAGE HEIGHT	116,0 cm	NET WEIGHT	162,0000 kg
GROSS WEIGHT	186,0000 kg	VOLUME	0,9900 m ³
HARMONISED CODE	84198180		

ACCESSORIES

220590	EXTRA OVEN GRID GN2/1 (53X63CM)
319010	REAR COVERING PANEL FOR CABINET (L=80CM)
399569	ADJUSTABLE WATER TAP FOR KITCHENS WITH A FLUE
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)
619012	GN2/1 INOX TRAY

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00