

316122

PP4E9

ELECTRIC SOLID BOILING TOP (TOP VERSION)



- Electric solid top (40 cm) with 2 independent zones.
- Electric solid tops and cookers are suitable for indirect cooking only.
- Overflow-proof worktop with raised and welded edges.
- Non-deformable, molybdenum steel plate (15 mm thick) with prolonged heat retention properties.
- Ultra-rapid infrared heating elements fixed under the plate with a power of 3.5 kW for each independent zone.
- Maximum temperature of 470°C.
- Thermostatic regulation.
- Temperature limiter inside the plates to reduce energy consumption.
- Heating and control commands specific for each zone.
- Safety thermostat.
- Lights warning when the heating areas are active.
- Height-adjustable rubberised plastic feet (15-25 mm)
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the electrical network.



TECHNICAL DATA

TOTAL POWER	7 kW	ELECTRIC POWER	7 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
BOILING TOP POWER	7 kW	COOKING ZONE POWER	2x3,5 n°- kW
ELECTRIC PLATE DIMENSIONS	37,4x72 cm	NUMBER OF COOKING ZONES	n° 2
PLATE TEMPERATURE RANGE	MAX 450 °C	MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm ²
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Iron and molybdenum
HEATING ZONES	n° 2	ELECTRICAL CONNECTION HEIGHT (H)	35 mm
ELECTRICAL CONNECTION HEIGHT (X)	329 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	15 mm	FOOT ADJUSTMENT	15/25 mm
IPX RATING	4	WIDTH	40 cm
DEPTH	90 cm	HEIGHT	28 cm
PACKAGE WIDTH	100,0 cm	PACKAGE DEPTH	46,0 cm
PACKAGE HEIGHT	58,0 cm	NET WEIGHT	60,0000 kg
GROSS WEIGHT	69,0000 kg	VOLUME	0,2600 m ³
HARMONISED CODE	84198180		

ACCESSORIES

- 399516 ADJUSTABLE WATER TAP
 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00