


316125

PPF8VE9

ELECTRIC SOLID BOILING TOP ON GN1/1 ELECTRIC CONVECTION OVEN WITH 1 GRID





- Electric solid top cooker (80 cm) with 4 independent zones on a GN 1/1 electric convection oven.
- Electric solid tops and cookers are suitable for indirect cooking only.
- Overflow-proof worktop with raised and welded edges.
- Non-deformable, molybdenum steel zone (15 mm thick) with prolonged heat retention properties.
- Ultra-rapid infrared heating elements fixed under the zone with a power of 3.5 kW for each independent zone.
- Maximum temperature of 470°C.
- Thermostatic regulation.
- Temperature limiter inside the zones to reduce energy consumption.
- Heating and control commands specific for each zone.
- Safety thermostat.
- Lights warning when the heating zones are active.
 - GN 1/1 ELECTRIC CONVECTION OVEN
 - >> AISI 304 stainless steel oven door.
- >> Stainless steel cooking chamber and long-lasting steel mesh and glass fibre gasket resistant to high temperatures.
- Heating through 2 fans with 2 heating elements with thermostatic control 60-270°C.
 - >> Stainless steel removable side tray racks.
 - >> 1 grid included.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the electrical network.



162,0000 kg

0,9900 m³

TECHNICAL DATA			
TOTAL POWER	19 kW	ELECTRIC POWER	19 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
OVEN POWER	5 kW	BOILING TOP POWER	14 kW
COOKING ZONE POWER	4X3,5 n°- kW	TRAY CAPACITY	n° 5xGN1/1
COOKING CHAMBER DIMENSIONS	57x51,5x30 cm	OVEN DIMENSIONS	GN1/1
ELECTRIC PLATE DIMENSIONS	77x68,4 cm	GUIDES	n° 5
NUMBER OF COOKING ZONES	n° 4	VERTICAL DISTANCE BETWEEN TRAYS	5 cm
OVEN TEMPERATURE RANGE	60÷270 °C	PLATE TEMPERATURE RANGE	MAX 450 °C
MINIMUM POWER CABLE CROSS-SECTION	5 x 6 n° - mm²	ELECTRIC CABLE TYPE	H07 RN-F
OVEN TYPE	Convection	PLATE TYPE	Iron and molybdenum
HEATING ZONES	n° 4	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	86,0 cm	PACKAGE DEPTH	100,0 cm

NET WEIGHT

VOLUME

ACCESSORIES

PACKAGE HEIGHT

HARMONISED CODE

GROSS WEIGHT

319010 REAR COVERING PANEL FOR CABINET (L=80CM)

399569 ADJUSTABLE WATER TAP FOR KITCHENS WITH A FLUE

399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

116,0 cm

183,2 kg 84198180

619004 EXTRA OVEN GRID GN1/1 (53X47CM)



INSTALLATION SCHEMES

