
316138

PCU4E9

ELECTRIC BOILING TOP WITH 2 SQUARED TILTING PLATES (30X30 CM - 11.8X11.8 IN, TOP VERSION)



- Boiling top (40 cm) with 2 coplanar, tilting, electric plates.
- Coplanar, tilting, squared, cast iron electric plates (30x30 cm and 8 mm thick) not hermetically sealed to the worktop.
- 3 kW power for each plate adjustable to 6 levels.
- Temperature limiter inside the plates to reduce energy consumption.
- Heating and control commands specific for each plate.
- Lights warning when the plates are on.
- Drawer to collect cooking residue.
- Setup for installing a water tap.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to make easy the connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	6 kW	ELECTRIC POWER	6 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 2N ~ V
BOILING TOP POWER	6 kW	COOKING ZONE POWER	2X3 n°- kW
ELECTRIC PLATE DIMENSIONS	30x30 cm	NUMBER OF COOKING ZONES	n° 2
MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm ²	ELECTRIC CABLE TYPE	H07 RN-F
ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	IPX RATING	4
WIDTH	40 cm	DEPTH	90 cm
HEIGHT	28 cm	PACKAGE WIDTH	100,0 cm
PACKAGE DEPTH	46,0 cm	PACKAGE HEIGHT	58,0 cm
NET WEIGHT	51 kg	GROSS WEIGHT	65 kg
VOLUME	0,26 m ³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	480.0 W	SENSIBLE HEAT RELEASE	1200.0 W
STEAM RELEASE	708.0 g/h		

ACCESSORIES

- 399516 ADJUSTABLE WATER TAP
 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00