
316151**PCCM8FE9****FREESTANDING GLASS CERAMIC ELECTRIC
BOILING TOP WITH 2 HEATING ZONES ON OPEN
CABINET**



- Freestanding glass ceramic electric boiling top on an open cabinet (80x45 cm) with 2 independent cooking zones.
- Mosaico90 is a special line of modular units, 45 cm deep, which combine perfectly with the Tecno90 range to create compact cooking islands designed to make the best use of space.
- AISI 304 stainless steel worktop (20/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel and side panels.
- Glass ceramic top (6 mm thick) hermetically sealed to the worktop for maximum hygiene and easy cleaning.
- Ultra-rapid infrared heating elements with 3.4 kW power for each independent zone.
- Energy regulator 0-6-infinite.
- Temperature limiter to prevent overheating.
- Heating and control commands specific for each zone by means of a thermostat.
- Lights warning when the heating zones are active.
- Warning lamps on the glass to enhance operator safety by signalling residual heat.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).

TECHNICAL DATA

TOTAL POWER	6,8 kW	ELECTRIC POWER	6,8 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 2N ~ V
BOILING TOP POWER	6,8 kW	COOKING ZONE POWER	2x3,4 n°- kW
2-ZONE HEATING ELEMENTS	n° 2	NUMBER OF COOKING ZONES	n° 2
MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm ²	ELECTRIC CABLE TYPE	H07 RN-F
HEATING ZONES	n° 2	ELECTRICAL CONNECTION HEIGHT (Y)	-45 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	45 cm	HEIGHT	90 cm
PACKAGE WIDTH	84 cm	PACKAGE DEPTH	52 cm
PACKAGE HEIGHT	116 cm	NET WEIGHT	59 kg
GROSS WEIGHT	71,5 kg	VOLUME	0,51 m ³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	544.0 W
SENSIBLE HEAT RELEASE	1360.0 W	STEAM RELEASE	802.4 g/h

ACCESSORIES

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

INSTALLATION SCHEMES

