

---

**316153**

PINM8FE9

**2-ZONE FREESTANDING INDUCTION BOILING TOP  
ON OPEN CABINET**

---



- Freestanding induction boiling top on an open cabinet (80x45 cm) with 2 independent cooking zones.
- Mosaico90 is a special line of modular units, 45 cm deep, which combine perfectly with the Tecno90 range to create compact cooking islands designed to make the best use of space.
- AISI 304 stainless steel worktop (20/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel and side panels.
- Glass ceramic boiling top (6 mm thick) hermetically sealed to the worktop for maximum hygiene and easy cleaning.
- 5 kW independent cooking zones each.
- Power regulator 0-6-infinite.
- Increased heating speed compared to other boiling top types.
- Heating is enabled only when in contact with the pan, saving energy and reducing overheating.
- Front air filter drawer easily accessible for cleaning and replacement.
- LED lights for detecting pans and signalling operation and errors.
- To optimise efficiency, use high-quality induction cookware with a base diameter ranging between 12 cm and 32 cm.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).

## TECHNICAL DATA

|                                   |                              |                                  |           |
|-----------------------------------|------------------------------|----------------------------------|-----------|
| TOTAL POWER                       | 10 kW                        | ELECTRIC POWER                   | 10 kW     |
| FREQUENCY                         | 50/60 Hz                     | VOLTAGE                          | 400 3 ~ V |
| COOKING ZONE POWER                | 2X5 n°- kW                   | NUMBER OF COOKING ZONES          | n° 2      |
| MINIMUM POWER CABLE CROSS-SECTION | 4 x 1,5 n° - mm <sup>2</sup> | ELECTRIC CABLE TYPE              | H07 RN-F  |
| ELECTRICAL CONNECTION HEIGHT (H)  | 486 mm                       | ELECTRICAL CONNECTION HEIGHT (X) | 122 mm    |
| ELECTRICAL CONNECTION HEIGHT (Y)  | -45 mm                       | FOOT HEIGHT                      | 133 mm    |
| FOOT ADJUSTMENT                   | 133/195 mm                   | IPX RATING                       | 4         |
| WIDTH                             | 80 cm                        | DEPTH                            | 45 cm     |
| HEIGHT                            | 90 cm                        | PACKAGE WIDTH                    | 86 cm     |
| PACKAGE DEPTH                     | 53 cm                        | PACKAGE HEIGHT                   | 114 cm    |
| NET WEIGHT                        | 43,1 kg                      | GROSS WEIGHT                     | 55,6 kg   |
| VOLUME                            | 0,52 m <sup>3</sup>          | HARMONISED CODE                  | 84198180  |
| LATENT HEAT RELEASE               | 280.0 W                      | SENSIBLE HEAT RELEASE            | 700.0 W   |
| STEAM RELEASE                     | 410.0 g/h                    |                                  |           |

## ACCESSORIES

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

INSTALLATION SCHEMES

