

316197

B12MFXEN9

**FREESTANDING TILTING ELECTRIC BRATT PAN
120L WITH AN AISI 304 STAINLESS STEEL TANK ON
CLOSED CABINET - MOTORISED LIFTING
MECHANISM**



- Freestanding tilting electric bratt pan 120 L (120 cm). Motorised tank lifting.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- The bratt pan is intended to braise and prepare stews, sauces, risottos, pan-fried vegetables and cooking with minimal liquid. Use as a fryer is not allowed.
- Heating through armoured heating elements.
- AISI 304 tilting tank with a 12 mm bottom and 2 mm walls
- Thermostatic control 0-50-300°C
- Green light indicating voltage presence and orange light indicating heating element operation.
- Safety thermostat automatically cuts the mains power in the presence of a fault.
- Micro safety switch on the lifting mechanism: lifting the tank disconnects power from the heating elements.
- AISI 304 spring-balance lid with integrated handle and hinge.
- Water filling control on the front panel.
- Water inlet fixed on the rear of the worktop, outside the tank.
- AISI 304 height-adjustable feet (133/195 mm).

TECHNICAL DATA

TOTAL POWER	15 kW	ELECTRIC POWER	15 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
TEMPERATURE RANGE	45÷300 °C	TANK CAPACITY	120lt
TANK DIMENSIONS	109,8x56,4x20 cm	MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm ²
TANK BOTTOM THICKNESS	12 mm	DRAINING THE TANK	Manual tipping
ELECTRIC CABLE TYPE	H07 RN-F	TANK TYPE	AISI 304
WATER CONNECTION DIAMETER	1/2"	IPX RATING	4
WIDTH	120 cm	DEPTH	90 cm
HEIGHT	90 cm	PACKAGE WIDTH	130 cm
PACKAGE DEPTH	105 cm	PACKAGE HEIGHT	118 cm
NET WEIGHT	213 kg	GROSS WEIGHT	255 kg
VOLUME	1,61 m ³	HARMONISED CODE	84198180

ACCESSORIES

INSTALLATION SCHEMES

5.2 PIANTA ALLACCIAMENTO B12

LEGENDA:			
B	Allacciamento acqua	E	Allacciamento elettrico
		Q	Morsetto equipotenziale

