
316222

SP4FE9

**GN1/1 FREESTANDING ELECTRIC CHIP SCUTTLE
ON OPEN CABINET**



- Freestanding chip scuttle on an open cabinet (40 cm).
- Power: 1 kW.
- AISI 304 stainless steel height-adjustable feet (133/195 mm)
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Heating through a lamp with ceramic-cast infrared heating element.
- Supplied with removable GN 1/1 H150 mm container with false bottom for oil dripping, both in AISI 304 stainless steel.
- Energy regulator 1-6-Infinite.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	1 kW	ELECTRIC POWER	1 kW
FREQUENCY	50/60 Hz	VOLTAGE	220-240 ~ V
TANK CAPACITY	GN1/1	CABINET DIMENSIONS	33x76,1x39,5 cm
TANK DIMENSIONS	32,5x53x15 cm	MINIMUM POWER CABLE CROSS-SECTION	3 x 1,5 n° - mm ²
ELECTRIC CABLE TYPE	H07 RN-F	TANK TYPE	AISI 304
ELECTRICAL CONNECTION HEIGHT (H)	484 mm	ELECTRICAL CONNECTION HEIGHT (X)	329 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm	FOOT HEIGHT	133 mm
IPX RATING	4	WIDTH	40 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	100,0 cm	PACKAGE DEPTH	46,0 cm
PACKAGE HEIGHT	115,0 cm	NET WEIGHT	38,4 kg
GROSS WEIGHT	48,8 kg	VOLUME	0,5300 m ³
HARMONISED CODE	84198180		

ACCESSORIES

- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 319009 REAR COVERING PANEL FOR CABINET (L=40CM)
- 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00