


---

**316225****PIN4FE9N****2-ZONE FREESTANDING INDUCTION BOILING TOP  
ON OPEN CABINET**

---



- Freestanding induction boiling top (40 cm) with 2 independent cooking zones on an open cabinet.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Glass ceramic boiling top (6 mm thick) hermetically sealed to the top for maximum hygiene and ease of cleaning.
- 5 kW independent cooking zones each.
- Power regulator 0-6-infinite.
- Increased heating speed compared to other boiling top types.
- Heating is enabled only when in contact with the pan, saving energy and reducing overheating.
- Front air filter drawer easily accessible for cleaning and replacement.
- LED lights for detecting pans and signalling operation and errors.
- To optimise efficiency, use high-quality induction cookware with a base diameter ranging between 12 cm and 32 cm.
- Setup for installing a water tap.
- Technical compartment for easy connection to the electrical network.
- Avoid placing above ovens or refrigerated bases.

TECHNICAL DATA

|                                  |            |                                   |                  |
|----------------------------------|------------|-----------------------------------|------------------|
| TOTAL POWER                      | 10 kW      | ELECTRIC POWER                    | 10 kW            |
| FREQUENCY                        | 50/60 Hz   | VOLTAGE                           | 400 3 ~ V        |
| COOKING ZONE POWER               | 2x5 n°- kW | CABINET DIMENSIONS                | 33x76,1x39,5 cm  |
| NUMBER OF COOKING ZONES          | n° 2       | MINIMUM POWER CABLE CROSS-SECTION | 4 x 1,5 n° - mm² |
| ELECTRIC CABLE TYPE              | H07 RN-F   | MAXIMUM RELATIVE AIR HUMIDITY     | 30-90 %          |
| ELECTRICAL CONNECTION HEIGHT (H) | 484 mm     | ELECTRICAL CONNECTION HEIGHT (X)  | 329 mm           |
| ELECTRICAL CONNECTION HEIGHT (Y) | -75 mm     | FOOT HEIGHT                       | 133 mm           |
| FOOT ADJUSTMENT                  | 133/195 mm | IPX RATING                        | 4                |
| WIDTH                            | 40 cm      | DEPTH                             | 90 cm            |
| HEIGHT                           | 90 cm      | PACKAGE WIDTH                     | 100,0 cm         |
| PACKAGE DEPTH                    | 46,0 cm    | PACKAGE HEIGHT                    | 115,0 cm         |
| NET WEIGHT                       | 42,6 kg    | GROSS WEIGHT                      | 57,6 kg          |
| VOLUME                           | 0,5300 m³  | HARMONISED CODE                   | 84198180         |
| LATENT HEAT RELEASE              | 280.0 W    | SENSIBLE HEAT RELEASE             | 700.0 W          |
| STEAM RELEASE                    | 410.0 g/h  |                                   |                  |

ACCESSORIES

- 319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
- 319009 REAR COVERING PANEL FOR CABINET (L=40CM)
- 399569 ADJUSTABLE WATER TAP FOR KITCHENS WITH A FLUE
- 399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00