
316250

FTL12E9

ELECTRIC GRIDDLE WITH SMOOTH PLATE (TOP VERSION)



- Electric griddle (120 cm), top version, with a smooth steel plate.
- The cooking plate, recessed and hermetically welded to the worktop, allows you to cook large quantities of different foods.
- 3 stainless steel burners (6 kW) with 3 independent cooking zones.
- Height-adjustable (15/25 mm) rubbed plastic feet.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

| | | | |
|----------------------------------|---------------------|-----------------------------------|------------------------------|
| TOTAL POWER | 18 kW | ELECTRIC POWER | 18 kW |
| FREQUENCY | 50/60 Hz | VOLTAGE | 380-415 3N~ V |
| TEMPERATURE RANGE | 60÷270 °C | MINIMUM POWER CABLE CROSS-SECTION | 5 x 2,5 n° - mm ² |
| COOKING SURFACE | 113x69 cm | ELECTRIC CABLE TYPE | H07 RN-F |
| PLATE TYPE | Smooth | HEATING ZONES | n° 3 |
| ELECTRICAL CONNECTION HEIGHT (H) | 35 mm | ELECTRICAL CONNECTION HEIGHT (X) | 1129 mm |
| ELECTRICAL CONNECTION HEIGHT (Y) | -75 mm | FOOT HEIGHT | 15 mm |
| FOOT ADJUSTMENT | 15/25 mm | IPX RATING | 4 |
| WIDTH | 120 cm | DEPTH | 90 cm |
| HEIGHT | 28 cm | PACKAGE WIDTH | 125 cm |
| PACKAGE DEPTH | 99 cm | PACKAGE HEIGHT | 54 cm |
| NET WEIGHT | 175 kg | GROSS WEIGHT | 190 kg |
| VOLUME | 0,66 m ³ | HARMONISED CODE | 84198180 |
| LATENT HEAT RELEASE | 7200.0 W | SENSIBLE HEAT RELEASE | 5940.0 W |
| STEAM RELEASE | 10584.0 g/h | | |

ACCESSORIES

| | |
|--------|---|
| 120595 | GRIDDLE-CLEANING SCRAPER |
| 120597 | SCRAPER - SPARE BLADE KIT (10 PCS) |
| 319002 | STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90 |
| 319009 | REAR COVERING PANEL FOR CABINET (L=40CM) |
| 399573 | PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM) |

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00