

316254

FTR12E9B

ELECTRIC GRIDDLE WITH A BRUSHED, CHROME-PLATED, 1/3 RIBBED PLATE (TOP VERSION)



- Electric griddle (120 cm), top version, with a brushed chrome-plated, 2/3 smooth and 1/3 ribbed cooking plate to cook a variety of products: from meat to fish and vegetables.
- The cooking plate recessed and hermetically welded to the worktop allows you to cook large quantities of different foods.
- The anti-scratch cooking plate ensures resistance to scratches and corrosion, while the striping enhances product grilling.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- The chrome-plated surface ensures less energy consumption and heat dispersion.
- 3 stainless steel burners (6 kW) with 3 independent working zones.
- Height-adjustable (15/25 mm) rubbered plastic feet.
- Scraper included.
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	18 kW	ELECTRIC POWER	18 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	60÷270 °C	MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm ²
COOKING SURFACE	113x69 cm	ELECTRIC CABLE TYPE	H07 RN-F
PLATE TYPE	Brushed chrome-plated - 1/3 ribbed and 2/3 smooth	HEATING ZONES	n° 3
ELECTRICAL CONNECTION HEIGHT (H)	35 mm	ELECTRICAL CONNECTION HEIGHT (X)	1129 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	IPX RATING	4
WIDTH	120 cm	DEPTH	90 cm
HEIGHT	28 cm	PACKAGE WIDTH	125 cm
PACKAGE DEPTH	99 cm	PACKAGE HEIGHT	54 cm
NET WEIGHT	175 kg	GROSS WEIGHT	190 kg
VOLUME	0,66 m ³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	7200.0 W	SENSIBLE HEAT RELEASE	5940.0 W
STEAM RELEASE	10584.0 g/h		

ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
319002	STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
319009	REAR COVERING PANEL FOR CABINET (L=40CM)
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES




Fig.1 | Abb.1 | pvc.1 - 5415.561.00