

316268

FTC4FE9

FREESTANDING ELECTRIC GRIDDLE WITH CHROME-PLATED SMOOTH PLATE ON OPEN CABINET



- Freestanding electric griddle on an open cabinet (40 cm) with a mirror-polished chrome-plated, smooth cooking plate recommended for cooking delicate products.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- Scraper included
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

| | | | |
|-----------------------------------|------------------------------|----------------------------------|------------------------|
| TOTAL POWER | 6 kW | ELECTRIC POWER | 6 kW |
| FREQUENCY | 50/60 Hz | VOLTAGE | 380-415 3N~ V |
| TEMPERATURE RANGE | 50÷320 °C | CABINET DIMENSIONS | 33x76,1x39,5 cm |
| MINIMUM POWER CABLE CROSS-SECTION | 5 x 1,5 n° - mm ² | COOKING SURFACE | 34,9x69,8 cm |
| ELECTRIC CABLE TYPE | H07 RN-F | PLATE TYPE | Chrome-plated - smooth |
| HEATING ZONES | n° 1 | ELECTRICAL CONNECTION HEIGHT (H) | 484 mm |
| ELECTRICAL CONNECTION HEIGHT (X) | 329 mm | ELECTRICAL CONNECTION HEIGHT (Y) | -75 mm |
| FOOT HEIGHT | 133 mm | FOOT ADJUSTMENT | 133/195 mm |
| IPX RATING | 4 | WIDTH | 40 cm |
| DEPTH | 90 cm | HEIGHT | 90 cm |
| PACKAGE WIDTH | 100,0 cm | PACKAGE DEPTH | 46,0 cm |
| PACKAGE HEIGHT | 115,0 cm | NET WEIGHT | 66,6 kg |
| GROSS WEIGHT | 82 kg | VOLUME | 0,5300 m ³ |
| HARMONISED CODE | 84198180 | LATENT HEAT RELEASE | 2400.0 W |
| SENSIBLE HEAT RELEASE | 1980.0 W | STEAM RELEASE | 3528.0 g/h |

ACCESSORIES

| | |
|--------|---|
| 120595 | GRIDDLE-CLEANING SCRAPER |
| 120597 | SCRAPER - SPARE BLADE KIT (10 PCS) |
| 319002 | STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90 |
| 319009 | REAR COVERING PANEL FOR CABINET (L=40CM) |
| 319055 | SIDE HEAT PROTECTION DEVICE |
| 399573 | PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM) |

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00