

316273

FTR4BE9

ELECTRIC GRIDDLE WITH A BRUSHED, CHROME-PLATED, RIBBED PLATE (TOP VERSION)



- Electric griddle (40 cm), top version, with a brushed chrome-plated, ribbed cooking plate to cook a variety of products: from meat to fish and vegetables.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- The anti-scratch cooking plate ensures resistance to scratches and corrosion, while the striping enhances the grilling of various products.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- The chrome-plated surface ensures less energy consumption and heat dispersion.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

| | | | |
|----------------------------------|--------------------------------|-----------------------------------|------------------------------|
| TOTAL POWER | 6 kW | ELECTRIC POWER | 6 kW |
| FREQUENCY | 50/60 Hz | VOLTAGE | 380-415 3N~ V |
| TEMPERATURE RANGE | 50÷320 °C | MINIMUM POWER CABLE CROSS-SECTION | 5 x 1,5 n° - mm ² |
| COOKING SURFACE | 34,9x69,8 cm | ELECTRIC CABLE TYPE | H07 RN-F |
| PLATE TYPE | Brushed chrome-plated - ribbed | HEATING ZONES | n° 1 |
| ELECTRICAL CONNECTION HEIGHT (H) | 35 mm | ELECTRICAL CONNECTION HEIGHT (X) | 329 mm |
| ELECTRICAL CONNECTION HEIGHT (Y) | -75 mm | FOOT HEIGHT | 15 mm |
| FOOT ADJUSTMENT | 15/25 mm | IPX RATING | 4 |
| WIDTH | 40 cm | DEPTH | 90 cm |
| HEIGHT | 28 cm | PACKAGE WIDTH | 100,0 cm |
| PACKAGE DEPTH | 46,0 cm | PACKAGE HEIGHT | 58,0 cm |
| NET WEIGHT | 53,9 kg | GROSS WEIGHT | 62,9 kg |
| VOLUME | 0,2600 m ³ | HARMONISED CODE | 84198180 |
| LATENT HEAT RELEASE | 2400.0 W | SENSIBLE HEAT RELEASE | 1980.0 W |
| STEAM RELEASE | 3528.0 g/h | | |

ACCESSORIES

| | |
|--------|--|
| 120595 | GRIDDLE-CLEANING SCRAPER |
| 120597 | SCRAPER - SPARE BLADE KIT (10 PCS) |
| 319055 | SIDE HEAT PROTECTION DEVICE |
| 399573 | PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM) |

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00