

316274

FTL8BE9

ELECTRIC GRIDDLE WITH A BRUSHED, CHROME-PLATED SMOOTH PLATE (TOP VERSION)



- Electric griddle (80 cm), top version, with a brushed chrome-plated, smooth cooking plate to cook a variety of products: from meat to fish and vegetables.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- The anti-scratch cooking plate ensures resistance to scratches and corrosion, while the striping enhances product grilling.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- The chrome-plated surface ensures less energy consumption and heat dispersion.
- 2 independent cooking zones.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Scraper included.
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	12 kW	ELECTRIC POWER	12 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	50÷320 °C	MINIMUM POWER CABLE CROSS-SECTION	5 x 2,5 n° - mm ²
COOKING SURFACE	74,9x69,8 cm	ELECTRIC CABLE TYPE	H07 RN-F
PLATE TYPE	Brushed chrome-plated - smooth	HEATING ZONES	n° 2
ELECTRICAL CONNECTION HEIGHT (H)	35 mm	ELECTRICAL CONNECTION HEIGHT (X)	729 mm
ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	IPX RATING	4
WIDTH	80 cm	DEPTH	90 cm
HEIGHT	28 cm	PACKAGE WIDTH	86,0 cm
PACKAGE DEPTH	100,0 cm	PACKAGE HEIGHT	60,0 cm
NET WEIGHT	102,5000 kg	GROSS WEIGHT	120,0000 kg
VOLUME	0,5100 m ³	HARMONISED CODE	84198180
LATENT HEAT RELEASE	4800.0 W	SENSIBLE HEAT RELEASE	3960.0 W
STEAM RELEASE	7056.0 g/h		

ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
319055	SIDE HEAT PROTECTION DEVICE
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00