

316277

FTR4BFE9

## FREESTANDING ELECTRIC GRIDDLE WITH BRUSHED, CHROME-PLATED, RIBBED PLATE ON OPEN CABINET



- Freestanding electric griddle on an open cabinet (40 cm) with a brushed, chrome-plated, ribbed cooking plate to cook a variety of products: from meat to fish and vegetables.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- The anti-scratch cooking plate ensures resistance to scratches and corrosion, while the striping enhances product grilling.
- The non-stick plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- The chrome-plated surface ensures less energy consumption and heat dispersion.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network.

## TECHNICAL DATA

TOTAL POWER	6 kW	ELECTRIC POWER	6 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	50÷320 °C	CABINET DIMENSIONS	33x76,1x39,5 cm
MINIMUM POWER CABLE CROSS-SECTION	5 x 1,5 n° - mm <sup>2</sup>	COOKING SURFACE	34,9x69,8 cm
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Brushed chrome-plated - ribbed
HEATING ZONES	n° 1	ELECTRICAL CONNECTION HEIGHT (H)	484 mm
ELECTRICAL CONNECTION HEIGHT (X)	329 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	40 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	100,0 cm	PACKAGE DEPTH	46,0 cm
PACKAGE HEIGHT	115,0 cm	NET WEIGHT	68,6000 kg
GROSS WEIGHT	80,0000 kg	VOLUME	0,5300 m <sup>3</sup>
HARMONISED CODE	84198180	LATENT HEAT RELEASE	2400.0 W
SENSIBLE HEAT RELEASE	1980.0 W	STEAM RELEASE	3528.0 g/h

## ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
319002	STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
319009	REAR COVERING PANEL FOR CABINET (L=40CM)
319055	SIDE HEAT PROTECTION DEVICE
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES



Fig.1 | Abb.1 | pvc.1 - 5415.561.00