


613003

PC105G7

6-BURNER GAS BOILING TOP WITH CAST IRON GRIDS (TOP VERSION)





- 6-burner gas boiling top (105 cm top version).
- Deep drawn worktop featuring rounded corners to prevent overflows and ensure enhanced hygiene and easy cleaning. Made with AISI 304 stainless steel with Scotch Brite finish.
- High-efficiency cast iron burners and flame spreaders with a single ring (3.3 and 4.5 kW) and double ring (7.2 kW).
- Main burner ignition via pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grid to resist acids, acids, alkalis and flames.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Stainless steel control panel, side and back panels.
- Module coupling system with external side joints.
- Technical compartment to facilitate connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- •The equipment is delivered in accordance with the customer's specifications in terms of installed nozzles, even during testing. G20 natural gas is the standard configuration. In addition, spare nozzles are included should conversion be necessary on site.



TECHNICAL DATA

TOTAL POWER	30 kW	GAS POWER	30 kW
OPEN BURNER POWER	2x7,2+2x3,3+2x4,5 n°- kW	BOILING TOP POWER	30 kW
NATURAL GAS CONSUMPTION	3,17 m³/h	NUMBER OF BURNERS	n° 6
BOILING PAN SUPPORT	RAAF enamelled cast iron	CE GAS CERTIFICATE NUMBER	CE-0085BO0091
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	26 mm
GAS CONNECTION HEIGHT (X)	1007 mm	GAS CONNECTION HEIGHT (Y)	-78 mm
FOOT HEIGHT	25 mm	FOOT ADJUSTMENT	15/25 mm
WIDTH	105 cm	DEPTH	70 cm
HEIGHT	28 cm	PACKAGE WIDTH	110 cm
PACKAGE DEPTH	80 cm	PACKAGE HEIGHT	53,0 cm
NET WEIGHT	61 kg	GROSS WEIGHT	71 kg
VOLUME	0,4700 m ³	HARMONISED CODE	84198180
LPG CONSUMPTION	2.36 m³/h	LATENT HEAT RELEASE	3600.0 W
SENSIBLE HEAT RELEASE	9000.0 W	STEAM RELEASE	5280.0 g/h

ACCESSORIES

120655 PAN SUPPORT REDUCER

220585 JOINT



INSTALLATION SCHEMES

