
613113

FTC70G7

GAS GRIDDLE WITH A CHROME-PLATED, SMOOTH PLATE (TOP VERSION)



- Gas griddle (70 cm top version) with a mirror-polished, brushed, chrome-plated, smooth plate top recommended for cooking delicate foods like fish and vegetables.
- Horizontal cooking plate (12 cm thick), 2 independent work areas.
- The non-stick cooking plate ensures quick and effortless cleaning, prevents oxidation, and eliminates any flavour transfer.
- Heating through 2 7 kW 2-branch chrome-plated steel burners.
- Operating thermostatic valve with temperature ranging between 150°C and 300°C.
- Safety thermostat that triggers below 350°C.
- Scraper included.
- Height-adjustable rubberised plastic feet (15-25 mm).
- Chrome-plated griddles comply with EU Regulation 1935/2004 concerning food contact materials and articles which are intended to come into contact with food.
- Stainless steel control panel, side and back panels.
- Module coupling system with external side joints.
- Appliances intended for direct cooking.
- Cooking plate hermetically sealed to the worktop.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Grooving with a cap and removable drawer for collecting grease and liquids.
- Removable splashback on 3 sides included.
- Technical compartment for easy connection to the gas network.
- Gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The equipment is delivered in accordance with the customer's specifications in terms of installed nozzles, even during testing. G20 natural gas is the standard configuration. In addition, spare nozzles are included should conversion be necessary on site.

TECHNICAL DATA

TOTAL POWER	14 kW	GAS POWER	14 kW
TEMPERATURE RANGE	60÷300 °C	NATURAL GAS CONSUMPTION	1,48 m³/h
COOKING SURFACE	69,6x56,4 cm	PLATE TYPE	Chrome-plated - smooth
HEATING ZONES	n° 2	CE GAS CERTIFICATE NUMBER	CE-0085B00093
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	26 mm
GAS CONNECTION HEIGHT (X)	657 mm	GAS CONNECTION HEIGHT (Y)	-78 mm
FOOT HEIGHT	25 mm	FOOT ADJUSTMENT	15/25 mm
WIDTH	70 cm	DEPTH	70 cm
HEIGHT	28 cm	PACKAGE WIDTH	81 cm
PACKAGE DEPTH	76 cm	PACKAGE HEIGHT	54 cm
NET WEIGHT	53,5 kg	GROSS WEIGHT	63,5 kg
VOLUME	0,3300 m³	HARMONISED CODE	84198180
LPG CONSUMPTION	1.1 m³/h	LATENT HEAT RELEASE	5600.0 W
SENSIBLE HEAT RELEASE	4900.0 W	STEAM RELEASE	8232.0 g/h

ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
619005	PAIR OF JOINTS FOR GRIDDLES

INSTALLATION SCHEMES



IMMAGINE DA DEFINIRE