


**713006**

PCPG8G7

## 2-BURNER GAS BOILING TOP WITH CAST IRON GRID AND HEATING PLATE (TOP VERSION)



- Gas solid top (40 cm) and 2 open burners (40 cm), top version.
- Non-deformable cast iron plate (1 cm thick).
- Cast iron central burner (4.5 kW) to reach a temperature of 400°C at the plate centre, with pilot burner and safety thermocouple.
- Valved gas cock.
- Gas boiling top Hob with single-ring cast iron burners (3.3 kW) and double-ring burners (7.2 kW); ignition of the main burners through a pilot burner equipped with a safety thermocouple and pan support grids with enamelled cast iron grates to be resistant to acids, alkalis, and flames. enamelled cast iron pan support grids to resist acids, acids, alkalis and flames.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.



## TECHNICAL DATA

TOTAL POWER	15 kW	GAS POWER	15 kW
OPEN BURNER POWER	1x3,3 + 1x7,2 n°- kW	BOILING TOP POWER	15 kW
GAS PLATE POWER	1x4,5 n°- kW	NATURAL GAS CONSUMPTION	1,58 m³/h
ELECTRIC PLATE DIMENSIONS	30,9x55,4 cm	NUMBER OF BURNERS	n° 2 + 1 (plate)
BOILING PAN SUPPORT	RAAF enamelled cast iron	PLATE TYPE	Cast iron
HEATING ZONES	n° 1	CE GAS CERTIFICATE NUMBER	CE-0085BO0091
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	35 mm
GAS CONNECTION HEIGHT (X)	766 mm	GAS CONNECTION HEIGHT (Y)	-63 mm
FOOT HEIGHT	15 mm	FOOT ADJUSTMENT	15/25 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	70 cm	HEIGHT	28 cm
PACKAGE WIDTH	87,0 cm	PACKAGE DEPTH	81,0 cm
PACKAGE HEIGHT	55 cm	NET WEIGHT	69 kg
GROSS WEIGHT	78 kg	VOLUME	0,38 m³
HARMONISED CODE	84198180	LPG CONSUMPTION	1.18 m³/h
LATENT HEAT RELEASE	1800.0 W	SENSIBLE HEAT RELEASE	4500.0 W
STEAM RELEASE	2640.0 g/h		

## ACCESSORIES

799506 PAIR OF CLOSING ELEMENTS (L=70CM)

## INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 - 5415.649.00