
713090

PCGM4FG7/1

**FREESTANDING 1-BURNER GAS BOILING TOP WITH
A CAST IRON GRID ON OPEN CABINET**



- Freestanding 1-burner gas boiling top on an open cabinet (40x45 cm).
- High-efficiency cast iron burner and flame spreader with a single ring (3.3 kW).
- Mosaico74 is a special line of modular units, only 45 cm deep, which combine perfectly with the Tecno74 range to create compact cooking islands designed to make the best use of space.
- AISI 304 stainless steel worktop (15/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel. Stainless steel side and back panels.
- Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grid to resist acids, alkalis and flames.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are certified by German body DVGW and have passed the most stringent safety tests.
- Unless specified otherwise, the models in the price list are tested with G20 natural gas nozzles and include a set of nozzles for conversion to G30/G31 LPG gas or vice versa, based on customer order.

TECHNICAL DATA

TOTAL POWER	3,3 kW	GAS POWER	3,3 kW
OPEN BURNER POWER	1X3,3 n°- kW	BOILING TOP POWER	3,3 kW
NATURAL GAS CONSUMPTION	0,35 m³/h	CABINET DIMENSIONS	33X34X39,5 cm
NUMBER OF BURNERS	n° 1	BOILING PAN SUPPORT	RAAF enamelled cast iron
CE GAS CERTIFICATE NUMBER	CE-0085CR0045	GAS CONNECTION DIAMETER	1/2"G EN10226-1
GAS CONNECTION HEIGHT (H)	486 mm	GAS CONNECTION HEIGHT (X)	122 mm
GAS CONNECTION HEIGHT (Y)	-45 mm	FOOT HEIGHT	155 mm
FOOT ADJUSTMENT	155/250 mm	WIDTH	40 cm
DEPTH	45 cm	HEIGHT	90 cm
PACKAGE WIDTH	99 cm	PACKAGE DEPTH	47 cm
PACKAGE HEIGHT	69 cm	NET WEIGHT	24,1 kg
GROSS WEIGHT	32,6 kg	VOLUME	0,32 m³
HARMONISED CODE	84198180	LPG CONSUMPTION	0.26 m³/h
LATENT HEAT RELEASE	396.0 W	SENSIBLE HEAT RELEASE	990.0 W
STEAM RELEASE	580.8 g/h		

ACCESSORIES

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

INSTALLATION SCHEMES

