

713095

PCGM8FG7/3

FREESTANDING 2-BURNER GAS BOILING TOP WITH CAST IRON GRIDS ON OPEN CABINET



- Freestanding 2-burner gas boiling top on an open cabinet (80x45 cm).
- High-efficiency cast iron burners and flame spreaders with a single ring (3.3 kW) and double ring (7.2 kW).
- Mosaico74 is a special line of modular units, only 45 cm deep, which combine

perfectly with the Tecno74 range to create compact cooking islands designed to make the best use of space.

- AISI 304 stainless steel worktop (15/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel. Stainless steel side and back panels.
- Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- · Valved gas cock.
- Enamelled cast iron pan support grid to resist acids, acids, alkalis and flames.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are certified by German body DVGW and have passed the most stringent safety tests.
- Unless specified otherwise, the models in the price list are tested with G20 natural gas nozzles and include a set of nozzles for conversion to G30/G31 LPG gas or vice versa, based on customer order.

TECHNICAL DATA

GAS CONNECTION HEIGHT (X)

FOOT HEIGHT

PACKAGE WIDTH

PACKAGE HEIGHT

HARMONISED CODE

SENSIBLE HEAT RELEASE

GROSS WEIGHT

IPX RATING

DEPTH



TOTAL POWER	10,5 kW	GAS POWER	10,5 kW
OPEN BURNER POWER	1X3,3+1X7,2 n°- kW	BOILING TOP POWER	10,5 kW
NATURAL GAS CONSUMPTION	1,11 m³/h	LPG CONSUMPTION	0.83 m³/h
CABINET DIMENSIONS	73X34X39,5 cm	NUMBER OF BURNERS	n° 2
BOILING PAN SUPPORT	RAAF enamelled cast iron	CE GAS CERTIFICATE NUMBER	CE-0085CR0045
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	486 mm

GAS CONNECTION HEIGHT (Y)

FOOT ADJUSTMENT

PACKAGE DEPTH

STEAM RELEASE

LATENT HEAT RELEASE

NET WEIGHT

VOLUME

WIDTH

HEIGHT

-45 mm

80 cm

90 cm

52 cm

42,5 kg

0,51 m³

1260.0 W

1848.0 g/h

155/250 mm

ACCESSORIES

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

122 mm

155 mm

45 cm

84 cm

115 cm

52,2 kg

84198180

3150.0 W



INSTALLATION SCHEMES

