
713111**PCGM12FG7/3****FREESTANDING 3-BURNER GAS BOILING TOP WITH
CAST IRON GRIDS ON OPEN CABINET**



- Freestanding 3-burner gas boiling top on an open cabinet (120x45 cm).
- High-efficiency cast iron burners and flame spreaders: 1 single ring (4.5 kW) and 2 double ring (7.2 kW).
- Mosaico74 is a special line of modular units, only 45 cm deep, which combine perfectly with the Tecno74 range to create compact cooking islands designed to make the best use of space.
- AISI 304 stainless steel worktop (15/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel. Stainless steel side and back panels.
- Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grid to resist acids, alkalis and flames.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are certified by German body DVGW and have passed the most stringent safety tests.
- Unless specified otherwise, the models in the price list are tested with G20 natural gas nozzles and include a set of nozzles for conversion to G30/G31 LPG gas or vice versa, based on customer order.

TECHNICAL DATA

TOTAL POWER	18,9 kW	GAS POWER	18,9 kW
OPEN BURNER POWER	1X4,5 + 2X7,2 n°- kW	BOILING TOP POWER	18,9 kW
NATURAL GAS CONSUMPTION	2,00 m³/h	LPG CONSUMPTION	1.49 m³/h
CABINET DIMENSIONS	113X34X39,5 cm	NUMBER OF BURNERS	n° 3
BOILING PAN SUPPORT	RAAF enamelled cast iron	CE GAS CERTIFICATE NUMBER	CE-0085CR0045
GAS CONNECTION DIAMETER	1/2" G EN10226-1	GAS CONNECTION HEIGHT (H)	486 mm
GAS CONNECTION HEIGHT (X)	122 mm	GAS CONNECTION HEIGHT (Y)	-45 mm
FOOT HEIGHT	155 mm	FOOT ADJUSTMENT	155/250 mm
IPX RATING	4	WIDTH	120 cm
DEPTH	45 cm	HEIGHT	90 cm
PACKAGE WIDTH	126 cm	PACKAGE DEPTH	53 cm
PACKAGE HEIGHT	115 cm	NET WEIGHT	63 kg
GROSS WEIGHT	73,3 kg	VOLUME	0,76 m³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	2268.0 W
SENSIBLE HEAT RELEASE	5670.0 W	STEAM RELEASE	3326.4 g/h

ACCESSORIES

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

INSTALLATION SCHEMES



IMMAGINE DA DEFINIRE