

713170 FTL4G7

GAS GRIDDLE WITH SMOOTH PLATE TOP



- Gas griddle (40 cm), top version, with smooth plate top.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (12 mm thick) to facilitate the drainage of grease and liquids.
- Heating through 1 2-branch chrome-plated steel burner (7 kW).
- Valved gas cock with maximum temperature of 390°C.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- \bullet The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.



TECHNICAL DATA

TOTAL POWER	7 kW	GAS POWER	7 kW
NATURAL GAS CONSUMPTION	0,74 m³/h	COOKING SURFACE	35,3x56,4 cm
PLATE TYPE	Smooth	HEATING ZONES	n° 1
CE GAS CERTIFICATE NUMBER	CE-0085BO0093	GAS CONNECTION DIAMETER	1/2"G EN10226-1
GAS CONNECTION HEIGHT (H)	35 mm	GAS CONNECTION HEIGHT (X)	366 mm
GAS CONNECTION HEIGHT (Y)	-63 mm	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	WIDTH	40 cm
DEPTH	70 cm	HEIGHT	28 cm
PACKAGE WIDTH	82 cm	PACKAGE DEPTH	47 cm
PACKAGE HEIGHT	56 cm	NET WEIGHT	40 kg
GROSS WEIGHT	46,5 kg	VOLUME	0,21 m³
HARMONISED CODE	84198180	LPG CONSUMPTION	0.55 m³/h
LATENT HEAT RELEASE	2800.0 W	SENSIBLE HEAT RELEASE	2450.0 W
STEAM RELEASE	4116.0 g/h		

ACCESSORIES

120595 GRIDDLE-CLEANING SCRAPER

120597 SCRAPER - SPARE BLADE KIT (10 PCS) 799506 PAIR OF CLOSING ELEMENTS (L=70CM)



INSTALLATION SCHEMES




Fig.1 | Abb.1 | рис.1 - 5415.649.00