

---

**713173****FTL8G7****GAS GRIDDLE WITH SMOOTH PLATE TOP**

---



- Gas griddle (80 cm), top version, with a smooth steel cooking plate.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (12 mm thick) to facilitate the drainage of grease and liquids.
- Heating through 2 2-branch chrome-plated steel burners (7 kW) with 2 independent working zones.
- Valved gas cock with maximum temperature of 390°C.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

## TECHNICAL DATA

|                           |               |                           |                 |
|---------------------------|---------------|---------------------------|-----------------|
| TOTAL POWER               | 14 kW         | GAS POWER                 | 14 kW           |
| NATURAL GAS CONSUMPTION   | 1,48 m³/h     | COOKING SURFACE           | 74,8x56,4 cm    |
| PLATE TYPE                | Smooth        | HEATING ZONES             | n° 2            |
| CE GAS CERTIFICATE NUMBER | CE-0085BO0093 | GAS CONNECTION DIAMETER   | 1/2"G EN10226-1 |
| GAS CONNECTION HEIGHT (H) | 35 mm         | GAS CONNECTION HEIGHT (X) | 766 mm          |
| GAS CONNECTION HEIGHT (Y) | -63 mm        | FOOT HEIGHT               | 15 mm           |
| FOOT ADJUSTMENT           | 15/25 mm      | WIDTH                     | 80 cm           |
| DEPTH                     | 70 cm         | HEIGHT                    | 28 cm           |
| PACKAGE WIDTH             | 87,0 cm       | PACKAGE DEPTH             | 81,0 cm         |
| PACKAGE HEIGHT            | 54 cm         | NET WEIGHT                | 81,2000 kg      |
| GROSS WEIGHT              | 88,6 kg       | VOLUME                    | 0,37 m³         |
| HARMONISED CODE           | 84198180      | LPG CONSUMPTION           | 1.1 m³/h        |
| LATENT HEAT RELEASE       | 5600.0 W      | SENSIBLE HEAT RELEASE     | 4900.0 W        |
| STEAM RELEASE             | 8232.0 g/h    |                           |                 |

## ACCESSORIES

|        |                                    |
|--------|------------------------------------|
| 120595 | GRIDDLE-CLEANING SCRAPER           |
| 120597 | SCRAPER - SPARE BLADE KIT (10 PCS) |
| 799506 | PAIR OF CLOSING ELEMENTS (L=70CM)  |

## INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 - 5415.649.00