

713178

FTR4FG7

FREESTANDING GAS GRIDDLE WITH RIBBED PLATE ON OPEN CABINET



- Freestanding gas griddle with a ribbed steel cooking plate on an open cabinet (40 cm).
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Sloped cooking plate (12 mm thick) to facilitate the drainage of grease and liquids.
- Heating through 1 2-branch chrome-plated steel burner (7 kW).
- Valved gas cock with maximum temperature of 390°C.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Ignition through a piezoelectric device with a water protection cap.
- Pilot burner and safety thermocouple.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECHNICAL DATA

| | | | |
|---------------------------|------------------------|---------------------------|-----------------|
| TOTAL POWER | 7 kW | GAS POWER | 7 kW |
| NATURAL GAS CONSUMPTION | 0,74 m ³ /h | CABINET DIMENSIONS | 33x57,4x39,5 cm |
| COOKING SURFACE | 35,3x56,4 cm | PLATE TYPE | Ribbed |
| HEATING ZONES | n° 1 | CE GAS CERTIFICATE NUMBER | CE-0085B00093 |
| GAS CONNECTION DIAMETER | 1/2"G EN10226-1 | GAS CONNECTION HEIGHT (H) | 660 mm |
| GAS CONNECTION HEIGHT (X) | 366 mm | GAS CONNECTION HEIGHT (Y) | -63 mm |
| FOOT HEIGHT | 155 mm | FOOT ADJUSTMENT | 155/250 mm |
| WIDTH | 40 cm | DEPTH | 70 cm |
| HEIGHT | 90 cm | PACKAGE WIDTH | 80 cm |
| PACKAGE DEPTH | 47 cm | PACKAGE HEIGHT | 115 cm |
| NET WEIGHT | 53 kg | GROSS WEIGHT | 63 kg |
| VOLUME | 0,4300 m ³ | HARMONISED CODE | 84198180 |
| LPG CONSUMPTION | 0.55 m ³ /h | LATENT HEAT RELEASE | 2800.0 W |
| SENSIBLE HEAT RELEASE | 2450.0 W | STEAM RELEASE | 4116.0 g/h |

ACCESSORIES

| | |
|--------|---|
| 120595 | GRIDDLE-CLEANING SCRAPER |
| 120597 | SCRAPER - SPARE BLADE KIT (10 PCS) |
| 319002 | STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90 |
| 719004 | TECNO74 REAR COVERING PANEL FOR FREESTANDING ELEMENTS (L=40CM) |
| 799503 | SIDE COVERING PANEL FOR FREESTANDING MODULE |
| 799506 | PAIR OF CLOSING ELEMENTS (L=70CM) |

INSTALLATION SCHEMES



Fig.1 | Abb.1 | рис.1 - 5415.649.00